

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. R. 15 W.	I-5; I-6; I-7
2. PROPERTY CONTROLLING IN SECTION 14	T. 24 N. R. 15 W.	12
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May 22, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and/or evidence and/or subsequent restoration:

C. (continued)

12

Set 1"x36" pipe & cedar post w/loc. tag
7" Maple N81°E 27.5
6" Maple S10°E 31.0
8" Cherry S59°W 25.2
Single strand B-W in witness tree NE

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-5 Found 1" iron in "T" road intersection E-W-S.

I-6 Restored corner per Millard survey; 33.0 westerly off found 1½" pipe, on testimony of Otto Miller age 70±, lived here 40 years. It should be in line with fence W and probably in Q county road N-S. Corner does fall in ctr. of N-S co. rd. and is 2' S of fence to W.

I-7 Found 1" pipe in trail road intersection E & N, that fits J.H. Millard witness of 1907.

12 Established corner equidistant and on line between center of Section to N and ¼ corner to S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-5

I-6

I-7

Found 1" iron rod in blacktop rd.	Set 1½"x36" pipe	Found 1" Pipe
7" Maple N20°E 51.12	9" Maple S86°E 35.96	10" Maple N44°W 40.51
6" Cherry N64°E 67.50	5" Maple N62°E 55.78	30" Maple N56°E 35.10
29" Maple S60°E 116.26	5" Ash S70°E 41.66	17" Maple S50°W 52.52
Set cedar post w/loc. tag	Set cedar post w/loc. tag	Set cedar post w/loc. tag
S45°W 47'	Due E 33'	Due S 33'

SIGNED BY

Carl F. Roser 9-4-75

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO.

PLEASANTON TOWNSHIP
MANISTEE COUNTY