

SURVEY &
REMONUMENTATION

MECOSTA COUNTY REMONUMENTATION PROGRAM

APR 04 1996

CORNER APPROVED BY PEER GROUP ON MAY 18, 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

Joanne Brown
Register of Deeds
Mecosta County

'95 NOV -2 A11:13

For corners in

Mecosta

(County)

Located in:

Corner Code #

1. Public Land Survey Sec 22 T 15 R 7 G-8
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

I, James J. Keller, in a field survey on February 19 95,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

July 20 1838, Noah Brookfield, Deputy Surveyor, GLO Notes, (Pg. 95 & 96) "Set 1/4 Sec. post", Beech 12" N43°E 37
Links, Beech 10" S86°W 8 Links

1895 - 1896 Lyman W. June, County Surveyor, Dry pine 24" S60°E 15 Links, Cedar S3°W 8 Links, Hemlock Stub for corner.
1940 M-66 Road Plans, Project 54-23

1976 Fluharty # 18223, Found 1/2" Iron in Mon Box, Telephone Pole S76°W 70.95', East end stone wall N17°W 77.52', Mail
Box post N17°W 77.50'

February 12, 1979, Thomas J. Mueller, #25861 (LCRC Liber 1 Page 474) (Recorded survey Liber 10 Page 778) Found 1/2"
Iron in Mon. Box in centerline M-66, Telephone Pole S76°W 70.95', East end Stone Wall N32°W 66.95', Mail Box
post N17°W 77.52'.

APPROVED BY MECOSTA CO. PEER GROUP
IN ACCORDANCE WITH P.A. 345 of 1990

James J. Keller
CHAIRMAN
DATE MAY 18, 1995

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

December 16 1991 James J. Keller found 5/8" Rebar 1.40' long in Monument Box in Centerline M-66. At 1.80 found
remanants of very old Iron bar. These remains could be found to a depth of 2.4'.

Found form nail in Telephone pole S81°W 71.26'

Set Pk Nail South East Side Telephone Pole N70°E 61.33' (slope measure)

East corner black stone in wall N25°W 66.98'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Remonumentation Monument in monument box and accepted as a careful and faithful perpetuation of the position of
the original corner.

Found form nail and set tag in Telephone pole S81°W 71.26'

Set Pk Nail and tag in South East Side Telephone Pole N70°E 61.33' (slope measure)

East corner black stone in wall N25°W 66.98'

Signed by

James J. Keller

Date

June 27 1995

Surveyor's Michigan License No. 10693

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1976

REVISED JAN., 1983

ADAPTED FOR WORD PROCESSING MARCH, 1993

LIBER 100

43

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

