LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 15 N. S., R. 1 E. W.	J-13; J-12;
2. PROPERTY CONTROLLING IN SECTION 35	T. 15 N. S., R. 1 E. W.	9
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 19, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

J-12

SET 5/8" ROD W/RLS CAP
4" RED MAPLE S87°W 6.6'
4" RED MAPLE N83°E 6.3'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-13 - FOUND 1 1/4" PIPE AT CORNER AS IDENTIFIED AND USED IN A 1968 SURVEY BY MERRIL HUNTER, R.L.S.

9 - SET BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

J-12 - SET CORNER BY STANDARD SURVEY PROCEDURE AT THE CALCULATED INTERSECTION OF THE TRUE 1/4 LINES.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-13

LEFT 1 1/4" PIPE IN PLACE
14" RED PINE N64°E 33.7'
9" RED OAK S17°E 19.4'

9

SET 5/8" ROD W/RLS CAP
8" RED MAPLE N55°W 20.0'
15" RED PINE S14°W 25.0'

SET 6" CEDAR POST W/LOC TAG BY CORNER

SIGNED BY Kenneth J Ostling DATE 10 - 25 - 84

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 (SEAL) REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ MIDLAND COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET