LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

| Surveyor's Name: Stephan J. Szyszkoski Fie | | <u>ki</u> Field Su | Survey Date: June 27, 2017 | | | | | |
|--|---|--|---|---------------------|---------------|--|--------------------------------------|----------------------------|
| For corner(s) in: | Marquette | County | A B | CDE | F G | н . | JKLN | — И, |
| Original Public Lar S 8 S S 5 Property Corner S S S S | T 45N R 29W T R T R T 45N R 29W T R T R T R T R T R T R T R T R T R T R | Corner Code MC btwn C3 and D3 on the west shore of the Michigamme River MC btwn C3 and D3 1/16 Corner Code | 2 6 3 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 | 8 17 20 29 | 9 16 21 28 33 | -1 5 -1 -22 -2 -27 -2 | 2 1 1 12 4 13 3 24 26 25 | 1 2 3 4 5 6 |
| Part A. Corner History | | | 13 A B | CDE | FG | HI | JKLN | 13 1 |

Meander Corner on the West (right) bank of the Michigamme River on the Section line between Sections 5 and 8. 1848 - Established by Wells Burt, Deputy, on the Section line between C3 and D3, 29.26 chains east of C3 and 10.86 chains west of D3. Set Black Cherry Meander Post. Y. Birch 6" N58W 26 links, Y.Birch 8" N80W 36 links.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

The original post and accessories were not recovered. There is a small slough at this location, bringing the westerly shore much closer to C3 than what is indicated by the GLO record. The record position for the corner is in the water at the confluence of the slough and the river. Apparently the slough either did not exist or was discounted or ignored in the original survey and the measurement was made to the riverbank proper and the MC was established at that point. As the GLO position for the corner is not accessible, I established a WITNESS CORNER to the Meander Corner on the west bank of the slough, 255.43' west of the proportionate position for the MC, 1696.90' east of C3 and 980.05' west of D3 and on a straight line between them. A search was also made for the original MC on the east bank of the river and it was not recovered.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

Set 1"IDx28" I.pipe with 2" alum. MDNR cap. 255.43' west of the record position of the Meander Corner Set measuring nail with MDNR tag in the side of: 12" Balsam N56°W 18.3' mrkd "WC BT" 6" Balsam S79°E 17.75' do
NW cor. block foundation of camp S56°E 36.55'
NW cor. sauna foundation S44°W 5.6'
West 129.92' Set 1"ID I.pipe with 2" alum. MDNR cap on the Section line.

PROFESSIONAL SURVEYOR No. 33986

STEPHAN J

SZYSZKOSKI

Bearings are magnetic.

Steph Insplied 07/06/2017

Professional Surveyor's License No.: 33986 page 1 of 1

Prepared By: S.J. Szyszkoski for the Michigan Dept. of Natural Resources, 427 N. US41 Baraga, MI 49908