

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 46 N. R. 27 W.	19, 110
2. PROPERTY CONTROLLING IN SECTION	27, T. 46 N. R. 27 W.	7, 14
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 10-29, 1986, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 19: Original monument and accessories not found.
 Corner 110: Original monument and accessories not found.
 Corner 7: Not set on original survey nor subsequently apparently.
 Corner 14: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 19: Restored by double proportion between corners north, south, west and river east.
 Corner 110: Restored midway and on line between corners north and south.
 Corner 7: Established midway and one line between corners north and south.
 Corner 14: Established midway and one line between corners north and south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 19: Set 1" I.D. by 32" I.P. w/4" alum. cap. 5" maple S07E 32.8ft. S26, NBT 10" jack pine N63E 50.0ft. S23, NBT 5" jack pine N37W 39.9ft. S22, NBT	Corner 7: Set 1" I.D. by 32" I.P. w/4" alum. cap. 10" oak N35E 8.4ft. 1/16S, BT 7" maple S22W 8.8ft. 1/16S, BT 10" maple S49E 45.9ft. 1/16S, BT
Corner 110: Set 1" I.D. by 32" I.P. w/4" alum. cap. 8" white pine N30E 37.8ft. 1/4S, NBT 6" white pine N22W 15.5ft. 1/4S, NBT 3" white pine S55W 8.4ft. 1/4S, NBT	Corner 14: Set 1" I.D. by 32" I.P. w/4" alum. cap. 7" maple S75E 25.4ft. 1/16S, BT 16" jack pine S84W 36.4ft. 1/16S, BT 7" aspen N10W 12.2ft. 1/16S, BT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY Michael Roose DATE 11-6-86

APPROVED AND SIGNED BY Keith L. Sackett DATE _____

MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 26, 1971
 REVISED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET