

1993

JOB NUMBER: 93300
SHEET NO. : 1-394

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
MARQUETTE
(County)

Located In:

Corner Code #

- | | | |
|------------------------------------|-----------------------------------|--|
| 1. Public Land Survey | 47N 27W | |
| | T _{46N} R _{27W} | |
| | T R | |
| | T R | |
| | T R | |
| 2. Property Controlling in Section | S T R | |
| | S T R | |
| 3. Miscellaneous Property in Sec. | S T R | |
| | S T R | |

C-1
C-13

LIBER

1 PAGE 102
Register of Deeds Stamp & File Number

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD
1993 DEC 30 PM 1:10
#

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, GERALD W. CARLSON, in a field survey on Wednesday, December 29, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

C-1: Section Corner common to Sections 5 and 6, T47N-R27W 1940 - C.C.I. Company North Lake Coordinates and Sections 31 and 32, T48N-R27W. 1846: Austin Burt's original survey notes describe the corner monument as a Sugar post referenced by:
16" Sugar N77.5E, 52 l
8" Fir N79W, 23 l
indicate the coordinates as S11.80, E5298.18. No description of the monument or corner accessories given.
No date given - The C.C.I. Company Triangulation Coordinate System indicates the coordinates as N236.49, W31514.64, marked by a 2" bolt 2' high. No corner accessories given.
C.C.I. aerial coordinates N238.00, W31512.59.
(See reverse side).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1993 - Found 1 1/2" diameter bolt 2.7' tall encased in concrete and stamped to identify the corner. Left the 1 1/2" diameter bolt as found. Distance West is 2642.82' (1.63' shorter than C.C.I. North Lake distance) and distance East is 5284.28' (2.53' shorter than C.C.I. North Lake distance). The angle checks within 00 01' 47" from the C.C.I. North Lake angle. Peer group ratification 12-20-93.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1993 - Existing 1 1/2" diameter bolt 2.7 ft. tall encased in concrete and stamped to identify the corner referenced by nails in:

- | | | | |
|-----------------|------|-----------|--------------------|
| 12" Maple | S03W | 31.20 ft. | Clark NBT |
| 10" White Birch | S68W | 17.37 ft. | Clark NBT |
| 6" Balsam | N19E | 19.61 ft. | Clark NBT (Spruce) |
| 4" Maple | S73E | 8.81 ft. | |

Monument is 2.7 ft. above ground, 115 ft. +/- North of an old railroad grade.
Stamped MCR - 1993 (Marquette County Remonumentation) in top of existing monument.
Bk. 5, Pg. 40



Signed by Gerald W. Carlson
24589

Date 12-30-93

Surveyor's Michigan License No. _____

Record No. 394

Part "A" Continued:

No date given - Marquette County Road Commission field book 636 indicates the corner as an iron bolt. No corner accessories given.

1981 - C.F. Clark found a 1 3/4" bolt with 3" cap nut 2' above grade stamped to identify the corner.

Referenced by:

16d nails in	10" White Birch	S85°W	17.58 ft.
	15" White Birch	S60°E	7.46 ft.
	10" Maple	South	31.25 ft.
	5" Spruce	N05°E	19.78 ft.

4 RC pg. 82.