SURVEY & REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filling Requirement of Act 74, Mich. P.A. 1970

MARQUETTE COUNTY MICHIGAN RECEIVED FOR RECORD

2000 DEC 18 PM 12: 44

Patricia	A.	Mone	less
REGISTE	ROF	DEEDS	Die.

For corners in	· ·		Dr ala 1
MARQUETTE	Located In:	Corner Code #	Fatricia (1. Montey)
(County)			Astricia A. Monley REGISTER OF DEEDS
1. Public Land Survey	T <u>47N</u> R <u>27W</u> TR TR		,
Property Controlling in Section S. Miscellaneous S. Property in Sec. S.	TR TR TR TR		LIBER ${f R}^2$ PAGE 266 Register of Deeds Stamp & File Numb
4. Lot No, Record	ied Plat		
5. Private Claims			
hereby state that under requirementioned in lines 1 and 2 above required in the current manual of sur Bureau of Land Management or benentioned in lines 3, 4 and 5 above Land Surveyors or by a Decree of recovered, found as expressed below	ents of P.A. 74, Michigan P./ were in conformance with re- rvey instructions of the United S by a decree of a Court of Lav e were in conformance with the of a Court of Law; established	gulations and rules therefore as states Department of the Interior, v and/or that the corner points e rules of the Michigan Board of d, re-established, monumented,	A B C D E F G H I J K I 2
on this certificate.			10 30 29 28 27 26 2
A. Description of original monu J-5; Quarter corner common to 1848: John Burt's original Subdi Ironwood quarter section post re 28" Hemlock N10E, 2	Sections 11 & 14. ivision survey notes describe	the corner monument as a set	RATIFIED BY PEER GRADER P.A. 345 OF 1990
1892: Cummings Survey of Sectionner of Section 11 to have been			DATE 11/27/00 East 2566.7'.
1899: Cummings survey of Sect	ion 14 recorded on page 22	8 indicates the North quarter cor	ner. Distance East 2566.7'.
No Date: CCI Coordinates Lists s 12765.32 and South 10265.23,	show two sets of coordinates. West 12769.08.	s for the South quarter corner of	Section 11; South 10264.12, West
1933: Marquette County Road C	commission Notes indicate m	ushroom on hill set by G.P. Cun	nmings September, 1892.
B. Description of corner evidence	ce found and/or method app	lied in restoring or reestablishing	corner:

J-5: 2000: No original corner evidence found. Found and accepted a 2" outside diameter iron pipe with a 11 ½" diameter mushroom tablet stamped to identify the corner projecting 1.4' above ground.

Description of monument for corner and accessories established to perpetuate locating the position of the corner: J-5: 2000: Accepted found monument as described in part B above and left it in place. Monument is referenced by:

W. Pine

N26W,

21.17

11" W. Pine

S61E,

J. Pine

S14E.

33.60'

8" Spruce S66W.

15.53 20.17

Distance East 2567.70', distance West 2686.97'.

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails,

24589

and stamped B.T. Tags affixed.

T47N-R27W

Corner Search Sheet

2000035

GERALD W CARLSON SURVEYOR No. 24589