

LAND CORNER RECORDATION CERTIFICATE

Authority: 1970 PA 74, MCL 54.205

Surveyor's Name: Stephan J. Szyszkoski

Field Survey Date: June 28, 2016

For corner(s) in: Marquette County

Original Public Land Survey Corner

Corner Code

S T R
S T R
S T R
S T R

Property Corner

1/16 Corner Code

a. S 28 T 48N R 28W
b. S 28 T 48N R 28W
S T R
S T R

6 (GCDB 360260)
5 (GCDB 340260)

Part A. Corner History

a.) Northeast 1/16 corner, Section 28. Not previously monumented.

b.) Center-North 1/16 corner, Section 28. Not previously monumented.

Part B: Surveyor's Report on Perpetuation, Restoration, Reestablishment, or Monumentation of Corner

a.) Established the position for the corner at the intersection of straight lines connecting opposite 1/16 corners, those to the west and south being monumented.

b.) Established the position for the corner midway and on a straight line between Quarter corner 1316.78' north and the intersection of 1/4 lines of Section 28, 1316.78' south.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

(a.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Maple N77°W 14.7' mrkd "1/16S BT"
4" Spruce N19°W 17.3' do
4" W.Birch N64°E 15.3' do
5" Balsam S16°E 3.2' do
Set sq'd cedar post adjacent.
E= 7938012.578 N= 194684.241

(b.) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
The mon. leans 0.1' E'ly due to rock. The cap marks the position for the corner. Set measuring nail with MDNR tag in the side of:
9" B.Spruce N01°W 10.35' mrkd "1/16S BT"
3" Balsam S47°E 15.0' do
5" Balsam S05°W 29.3' do
6" Balsam N67°W 11.1' do
Set sq'd cedar post adjacent.
E= 7937609.506 N= 194687.951

Bearings are magnetic. Coordinates are MCS83, NAD83(2011) Epoch 2010.00, in meter
Coordinate Reference: NGS PID AA8080, E= 7925456.741 m. N= 192972.689 m.

Stephan J. Szyszkoski 10/06/2016

