

**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Marquette	Located In:	Corner Code #
(County)		
1. Public Land Survey	T 48N R 29W	I9
	T _____ R _____	(GCDB 500300)
	T _____ R _____	
2. Property Controlling in Section	S _____ T _____ R _____	
	S _____ T _____ R _____	
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 09/17/14 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

Corner common to Sections 22-23-26-27. 1848 - Established by Wells Burt, Deputy. Set White Birch post. Aspen 12" S48°E 49 links, Spruce 8" N76°W 52 links. 2008 - Robert R. Spear PS found a 3/4"x1-1/2" flat top iron near the top of a rock knob with downed squared Balsam post adjacent and forester's location poster nearby. Mr. Spear used this position to calculate positions for J9 & I10 and a subdivision of the SE1/4 of Section 26. This monument was also previously found by Larry Bussone PS and Mr. Bussone used it to run some approximate forestry lines. No record found describing who placed this monument or when it was set. Mr. Spear's witnesses: Maple 6" N80°E 4.67'; Aspen 4" S25°W 18.31'; Balsam 6" N88°W 7.21'; Maple 6" N02°E 18.19'.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

Found a 1/2" iron rod with a 1-3/8" dia. flat top in accord with Mr. Spear's accessories. Extensive dependent retracement in the central part of this township in 2014 by the MI D.N.R. resulted in the conclusion that this monument is likely not the best evidence of the position of the original corner and that reliance upon the topographic features noted in the 1848 US field notes and measurements to adjacent corners results in the most reasonable position at which to reestablish the corner. Most notably, the distance from this monument to I11 is 61.5' short of the US record. In the central part of this township the north-south lines were regularly observed to measure short of the US record but, with the exception of one other line which clearly contains a blunder, the maximum observed deficiency is 33 feet. Further, the measure from this monument to reestablished I7 was found to be 5305.8', 25.8' longer than the US record. Additionally, the US record along Section lines north, east, and west from I9 contain well defined topographic feature calls which do not support the position of this monument as being the position of the original corner. After discussion with Mr. Spear and Mr. Bussone, during which they acquiesced in my rejection of this monument, I reestablished the position for the corner in accord with the US record to: Top of ledge 100' c.E&W 2.15 ch. north; Stream 10 c.S.W. 62.88 ch. north; Ascend ledge 40 ft. c.S.S.W. 5.7 ch. east; Descend ledge and hill 15.50 ch. east; West end of ledge c.E&W 12.1 ch. west; Descend hill 100 ft. 24.1 ch. west. The reestablished position is 4 ft. west of a straight line between monumented I7 & I11. Distance to I11 is 5255.2' (US=5280'); to I7 is 5269.1' (US=5280'); to G9 is 5253.1' (US=5284'); to K9 5267.5' (US=5282.6').

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

Set 1"IDx28" I.pipe with 2" alum. MDNR cap.	6" Sugar N32°W 16.95'	"S22 NBT"
Set measuring nail with MDNR tag in the side of:	1/2" iron with 1-3/8" top S14W 37.2'	
9" Maple N56°E 13.6'	mrkd "S23 NBT"	Set sq'd cedar post adjacent.
12" Oak S21°E 15.15'	"S26 NBT"	E= 7930377.271 N= 195169.793
5" Balsam S28°W 6.55'	"S27 NBT"	

**Bearings are magnetic.** Coordinates are MCS83 in meters (NAD83(2011) Datum)  
 Coord. Ref.=NGS PID AA8080: N= 192972.689 m. E= 7925456.741 m.

Signed by Stephan J. Szyszkoski Date 11/24/2014  
 Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

