SURVEY & REMONUMENTATION

MAY 2 2 1997

В.

Signed by

Surveyor's Michigan License No.

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74 Mich. B.A. 1979

For corners @Of	MMISSION	riling Requirement of Act 74, Mich. I	P.A. 1970
MARQUETTE	Located In:	Corner Code #	RECORDED Dec. 26 1997
(County)		Come: Code #	AT 4:30 O'CLOCK P.M
1. Public Land Si	IIDAY T.A	22 000	LIBER OF PAGE
4000 24114 01	·	NR 30W A-13	Fatricia a. Mantey
	T	R <u>A-1</u>	REGISTER OF DEEDS
Property Contr in Section Miscellaneous Property in Sec	ST ST	R	LIBER 1 PAGE 37
4.5			Register of Deeds Stamp & File Number
4. Lot No.	, Recorded Plat		
5. Private Claims	· · · · · · · · · · · · · · · · · · ·		ABCDEFGHIJKI
		-	2 6 5 1
ATAN K DIE	DOD	•	·
requirements of P A 7	in a field survey o	NOVEMBER, 19 96 do hereby state that orner points mentioned in lines 1 and 3 character	under 4 7 8 9 10 11
conformance with regul United States Departmental That the corner points in	lations and rules therefore as requent of the Interior, Bureau of Land	ulred in the current manual of survey instructions of Management or by a decree of a Court of Law ar	of the 5
ecovered, found as exp	pressed below:	ve were in conformance with the rules of the Mich t of Law; established, re-established, monume	inted, 7
NOTE: Not more th	on 2 on		8 -19 -20 -21 -22 -23 -24
NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate.			9
			10 30 29 28 27 26 25
			11
			12 31 32 33 34 35 36
. Description of original	ginal monument and access		13
	Anial mountileut and accesso	ories and/or subsequent restoration:	RATIFIED BY PEER GROUP
Corner con	mmon to Sections 1,6,31 and 36, T	47/48N - R30/31W	P.A. 345 OF 1990
A-13:		stin Burt D. S. set a wood post witnessed by: 1	2 Sugar Maple N37*E 68L; 11" Yellow Birch
Description of cor	3.62'; 12" Maple S50°E 17.9; Corner of Section 6 and M.C.	covered no identifiable original evidence and set I ssed by nails in: 10" Basswood N50'E 7.00'; 10 5'. Recorded in L.4R.C., Page 424. Single proport re-established from 2 recovered original bearing to tethod applied in restoring or reestablishing	" Basswood N62°W 13.93'; 12" Maple S57°W tionate measurement was between the Southwest
A-13:	1996; ECI recovered carne	d rehar on in 1004 av	;
		d rebar set in 1984. No original comer evider L.O. tetrain calls: North "descend hill" ECI 50'	
	ECI and G.L.O. 495'; East "a	second hill" (felt to be descend) ECI and G.L.O. 18" "ascend hill" ECI 2298' - G.L.O. 2395' South To	G.L.O. 66' (broad transition), "intersect lake"
	1173' (very broad transition),	"ascend hill" ECI 2298' - G.L.O. 2295'; South "u ". In assessing the establishment rationals used in	on hill" RCI 1064' - GLO 1014' - W
	ringe" ECI 431' - G.L.O. 462	". In assessing the establishment rationale used in	1984 including the very close provider
•	double proportionate management	al evidence and general concurrence with G.L.O. s not appropriate in this instance and concurrence.	measurements in all directions it is fall that
	Comer position established by	s not appropriate in this instance and concur with acceptance of capped rebar as a careful and faithful	the establishing surveyor in comer placement
-	comer. Distance North is 489 6	acceptance of capped rebar as a careful and faithful 3' and distance East is 2450.90'.	I reestablishment of the position of the original
Description of monu		ories established to perpetuate locating the	-
1996:		· ·	
	Replaced capped rebar with a 2-3/8" O.D. aluminum pipe capped with a 3-1/4" aluminum tablet Marquette County Survey monument stamped to identify the corner set about 0.6' above grade. Bearing trees are face, nail & butt blazed and painted yellow with B.T. tags attached. Butt blaze is scribed "B.T.". All 1984 trees were publicated as the state of the stat		
	yellow with B.T. tags attached.	Butt blaze is scribed "B T " AN 1004	rees are face, nail & butt blazed and painted
	nail with an orange washer stamp	Butt blaze is scribed "B.T.". All 1984 trees were used "ECI-30097" in the side of the tree. Bearings are	unized with distances measured from a duplex
		and sine of the tree. Bearings ar	re magnetic.
		12" Basswood N49°E 7.05° 14" Maple S50 14" Maple S58°W 3.51' 12" Basswood N60	re magnetic. PE 17.93' PW 13.91' ALAN

Steel fence post w/survey marker sign - North 1.7'.

PIERCE

LAND

SURVEYOR