

SURVEY &
REMONUMENTATION
APR 11 1995
COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Approved by Menominee County
Land Survey Remonumentation
Peer Group Under Act 345 Of
P.A. Of 1990 On 12/9, 199 94
MEL DAVIS RLS
ALTING Chairman

For corners in
MENOMINEE
(County)

Recorded In:

Corner Code ##

- | | | |
|---------------------------------------|---|-------------|
| 1. Public Land Survey | T <u>33N</u> R <u>27W</u> | <u>A-11</u> |
| | T <u> </u> R <u> </u> | <u> </u> |
| | T <u> </u> R <u> </u> | <u> </u> |
| | T <u> </u> R <u> </u> | <u> </u> |
| 2. Property Controlling
in Section | S <u> </u> T <u> </u> R <u> </u> | <u> </u> |
| | S <u> </u> T <u> </u> R <u> </u> | <u> </u> |
| 3. Miscellaneous
Property in Sec. | S <u> </u> T <u> </u> R <u> </u> | <u> </u> |
| | S <u> </u> T <u> </u> R <u> </u> | <u> </u> |

4. Lot No. , Recorded Plat
5. Private Claims

William Lenca

May 31

94

I, William Lenca, in a field survey on May 31, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1847: Original Survey (Township Exterior) by James H. Mullett - B.T.'s - Spruce, 6" - S45°E - 17 lks; Spruce, 8" - N17°E - 21 lks. All original evidence for this corner has been destroyed by County Road improvements.
- 1848: Original Survey (Section Subdivision) by John Mullett - B.T.'s - Cedar, 12" - S12°W - 20 lks; Spruce, 10" - N45°W - 24 lks. All original evidence for this corner has been destroyed by County Road improvements.
- 1901: Albert Haas, County Surveyor, made a survey of Section 25, T33N-R28W showing the location of this corner as it relates to other corners in this section. The survey states that a 4" Cedar Post was set from Government B.T. No new B.T.'s are given.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We found a Railroad Spike in the centerline of an intersection of county roads running North - South and West. Our measured distances to corners 1/2 mile north (2662.06 feet) and 1/2 mile West (2687.40 feet) match closely with the 1901 Haas Survey. The recorded distances are 2659.8 feet to the 1/4 Corner North and 2680.9 feet to the 1/4 Corner West. This position also fits well with existing occupation in the area and is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 24" Iron Rod/3-1/4" dia. Alum. cap stamped for corner location in Monument Box:

5" dia. Cedar	N39°E	62.21 feet	Scr. NBT
9" dia. Tamarack	S24°E	47.48 feet	Scr. NBT
5" dia. Tamarack	N16°W	97.90 feet	Scr. NBT
5/8" x 24" Iron Rod/2" dia. Alum. cap - WITNESS MARKER	S42°W	50.73 feet	
Survey Sign Post	S42°W	51.1 feet	

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca Date Nov. 18, 1994

Surveyor's Michigan License No. 26461

RECEIVED FOR RECORD
94 DEC 12 AM 8:55
PAGE # 108 BK. 4
BARBARA MORRISON
REGISTER OF DEEDS
MENOMINEE, MI 49858
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	N
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

