

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Menominee
(County)

Located In:

Corner Code ==

1. Public Land Survey T R
T R
T R
T R
2. Property Controlling S 13 T 34N R 26W 6, 8, 9.
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, David B. Babbitt, in a field survey on 6/16, 19 86,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

6. NE 1/16 corner of Section 13. Not previously established.
9. E1/16 corner on the E-W 1/4 line of Section 13. Not previously established.
8. W1/16 corner on the E-W 1/4 line of Section 13. Not previously established.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

6. Set at the computed center of the NE 1/4 of Section 13 by closed traverse.
9. Set M.P.O.L. between the East 1/4 corner and the center of Section 13.
8. Set M.P.O.L. between the West 1/4 corner and the center of Section 13.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- | | | |
|--------------------------|-----------------------|------------------------------|
| 6. D.N.R. Monument | 9. D.N.R. Monument | 8. D.N.R. Monument |
| 5" w.birch N57W, 1.70' | 8" ash N72W, 14.3' | 10" w.ash, N31E, 145.7' |
| 8" w.ash N34E, 8.5' | 5" cedar N85E, 33.3' | 12" scotch pine, S22E, 20.4' |
| 6" w.ash S46E, 23.42' | 9" cedar, S34E, 5.8' | 7" scotch pine, S11W, 14.3' |
| 13" r.maple S55W, 30.78' | 7" cedar, S63W, 12.9' | 3" h.maple, N87W, 150.75' |

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by David B. Babbitt Date 7-16-86

Surveyor's Michigan License No. RLS 21558