LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners i	n
---------------	---

	1
Menominee Located In:	Corner Code #
1. Public Land Survey T R T R	
TR	
2. Property Controlling S 11 T 34N R 29W in Section S T R	POL N-S1/4In
s T R	
3. Miscellaneous STTR	10
Property in Sec. S T R	Register of Deeds Stamp & File Number
4. Lot No. , Recorded Plat	A B C D E F G H I J K L M
5. Private Claims	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
I, Jeremy J. Pipp , in a field survey on 4/05/2013	3
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner	
above were in conformance with regulations and rules therefore as require	red in the current manual of survey 5
instructions of the United States Department of the Interior, Bureau of La a Court of Law and /or that the corner points mentioned in lines 3, 4 and	
the rules of the Michigan Board of Land Surveyors or by a Decree	
re-established, monumented, recovered, found as expressed below:	9
NOTE: Not more than 2 corners, all in the same town and range,	e, may be recorded
on this certificate.	11 32 33 34 35 36
	13
A. Description of original monument and accessories and/or s	subsequent restoration:
(POL N-S1/4 line) Point on North-South One	e-Quarter Line of Section 11 on left bank of
Escanaba River. Not set in original surve	rey, no evidence of subsequent establishment.
	·
B. Description of corner evidence found and/or method appli	lied in restoring or reestablishing corner:
	-
(DOL 14 04 14 75-2) E 1 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
bank of Escanaba River.	orth-South One-Quarter Line of Section 11 on left
bank of Loodhaba hityer.	
C. Description of monument for corner and accessories estab	hished to perpetuate locating the position of the common
	busined to perpetuate locating the position of the comer:
(POL N-S1/4 line) DNR monument 5" Ash N39E 51.87' (MC.BT)	
5" Ash N39E 51.87' (MC,BT) 32" Maple S63E 20.52' (MC,BT)	
22" Maple N49W 17.63' (MC,BT)	
36" Maple N14W 15.35' (MC,BT) All trees are blazed, scribed, and	
painted. Measurements are to nail in	
side of tree, bearings are magnetic.	
Signed by	Pate July 17, 2012
Surveyor's Michigan License No. 50447	
For the Michigan Department of Natural Res	
20060	FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 Revised Jan., 1983
	Rervised Oct., 1995