

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee (County)	Located In:	Corner Code #
1. Public Land Survey	T 34N R 29W	G04
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. , Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Jeremy J. Pipp, in a field survey on 4/03/2012AD do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(G04) Quarter Corner common to Sections 9 and 10. 1852: Francis Coleman, DS. Set post
witnessed by: B. Ash 6 N64W 40 links (26.40'); Elm 6 S55E 9 links (5.94').

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(G04) No evidence of original survey or subsequent restoration found. Corner position
reestablished along a line parallel with the East line of Section 10 and matching the
"best fit" position of the GLO meander notes to the to existing shoreline (matches well
through majority of Section 9). One-Quarter position established at record distance South
of the intersection of this parallel line with the line between Sections 3 & 10 (also
being the south line the Plat of Menominee Forest Estates #1). Position is accepted as a
careful and faithful REESTABLISHMENT of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(G04) DNR monument
9" Maple S49E 34.28' (1/4S,NBT)
12" Basswood S03W 53.09' (1/4S,NBT)
6" Elm S37W 37.37' (1/4S,NBT)
15" Ash N09W 11.97' (1/4S,NBT)

All trees are blazed, scribed, painted,
and signed. Measurements are to nail in
side of tree, bearings are magnetic. A
metal rail & sign were set North 1.5
feet.

Signed by

Surveyor's Michigan License No.

50447



July 17, 2012

For the Michigan Department of Natural Resources, Office of Land Engineering