

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee
(County)

Located In:

Corner Code #

1. Public Land Survey

T
T
T

R
R
R

2. Property Controlling
in Section

S 10

T 36N

R 25W

04

3. Miscellaneous
Property in Sec.

S
S
S

T
T
T

R
R
R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5			4		3		2		1
3													
4	7			8			9		10		11		12
5													
6	18			17			16		15		14		13
7													
8	19			20			21		22		23		24
9													
10	30			29			28		27		26		25
11													
12	31			32			33		34		35		36
13													

, Jeremy J. Pipp , in a field survey on 2/10/2014 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(04) Northwest One-Sixteenth corner of Section 10. Not set in original survey, no
evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(04) Corner position established at the intersection of the North and West One-Sixteenth
lines of Section 10.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(04) DNR monument
15" W. Pine N48E 57.97' (1/16S,BT)
5" Tamarack S38E 18.13' (1/16S,BT)
5" Spruce S53W 38.72' (1/16S,BT)
5" Spruce N56W 35.62' (1/16S,BT)
All trees are blazed, scribed, and
painted. Measurements are to nail in
side of tree, bearings are magnetic.

Signed by

Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources, Forest Res.

July 9, 2014

