

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

for corners in

Menominee (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S 21 T 36N R 28W	02
	S 21 T 36N R 28W	06
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

3/26/2013AD
3/26/2013AD
do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(02) East One-Sixteenth corner common to Sections 16 and 21. Not set in original survey, no evidence of subsequent establishment.

(06) Northeast One-Sixteenth corner of Section 21. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(02) Corner position established mid-point and on-line between the North One-Quarter corner and the Northeast corner of Section 21.

(06) Corner position established at the intersection of the North and East One-Sixteenth lines of Section 21.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(02) DNR monument
11" Maple N54E 8.97' (1/16S,BT)
8" Ironwood S41E 20.08' (1/16S,BT)
12" Maple S51W 8.13' (1/16S,BT)
EX 13" Maple N13W 15.20' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by _____
Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources, Forest Resource Division

(06) DNR monument
6" Maple N85E 34.74' (1/16S,BT)
7" Maple S32E 25.63' (1/16S,BT)
5" Maple WEST 33.23' (1/16S,BT)
5" Maple N08W 36.48' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Date July 30, 2013

