LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

or corners in

			l						
Menominee	Located In:	Corner Code #							
(County)	-								
. Public Land Survey	TR TR								
Property Controlling n Section	S 12 T 37N R 25W S 12 T 37N R 25W S T R	11 13	ļ						
3. Miscellaneous Property in Sec.	S T R S T R		Ber	gister of De	ede Sta	ımı & F	ile Nur	nher	
1. Lot No. , Red 5. Private Claims	corded Plat		1 A B	C D E	F G	н :	I J	K L	
	9/11/201	3AD	2 - 6	╼┼╌┆╼┤	- }-	<u></u> \$	{-	╂╌┆╸	
,Jeremy J. Pipp, in	a field survey on 9/17/201	3AD do hereby state	3 - 7					+	_
hat under requirements of P.A. 7	e I 1				,	0 (9		
bove were in conformance with regulations and rules therefore as required in the current manual of survey s								13	_
Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7 he rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, 8 19 20 21 22 23							24	_	
e-established, monumented, recovered, found as expressed below:								_	
NOTE: Not more than 2 corn	10 - 30	29	-28	27	-25-	25	_		
on this certificate.	12 -31	32	_3'3	-34-	35-	36	_		

- 4. Description of original monument and accessories and/or subsequent restoration:
- (11) Southwest One-Sixteenth corner of Section 12. Not set in original survey, no evidence of subsequent establishment.
- (13) Southeast One-Sixteenth corner of Section 12. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (11) Corner position established at the intersection of the South and West One-Sixteenth lines of Section 12.
- (13) Corner position established at the intersection of the South and East One-Sixteenth lines of Section 12.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11)	DNR monument	(13) DNR monument					
13" Maple	N50E 33.75' (1/16S,BT)	8" Tamarack NO8E 9.40' (1/16S,BT)					
8" Maple	S79E 26.22' (1/16S,BT)	8" Cedar S60E 12.10' (1/16S,BT)					
11" Maple	\$37W 20.60' (1/16\$,BT)	5" Cedar S79W 7.06' (1/16S,BT)					
6" Maple	N41W 6.17' (1/16S,BT)	6" Cedar N52W 13.50' (1/16S,BT)					
All trees a	re blazed, scribed, and	All trees are blazed, scribed, and					
	Measurements are to nail in	paintable Neasurements are to nail in side free bearings are magnetic.					
side of tre	ee, bearings are magnetic.	side of free bearings are magnetic.					

Summer Wighter Linear Ma

Feet PRO

October 1, 2013

Surveyor's Michigan License No.

For the Michigan Department of Natural R

"No"

Signed by