LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee	Located In:	Corner Code #			
(County)		0011101 0000 1/			
1. Public Land Survey	TR				
2. Property Controlling in Section	T R S 12 T 37N R 25W S T R S T R	12			
3. Miscellaneous Property in Sec.	S T R S T R		Posietar of D	anda Storra & File	a Blassada a a
4. Lot No. , Red	corded Plat		Register of De	eeds Stamp & File	Number
5. Private Claims			A B C D	EFGH	IJKLM
			2 - 65-	╃╾┇╾	┼╾┇╌╁╌┇╼┥
ı, _ Jeremy J. Pipp , in	a field survey on 9/17/20	13AD do homburator	3	 	
			4 - 7 - 8-		11-12-
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey 5					•
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 18 17 16 15 14 13					
	orner points mentioned in lines 3, 4 an				
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, 8				1 1 22	
re-established, monumented, recovered, found as expressed below:					
			9		
NOTE: Not more than 2 corners, all in the same town and range, may be recorded			10 30 29	28 27	26 -25
			11	 	
was grand what bit i had be a			12 31 32	33-1-34	35-36-
A. Description of original monument and accessories and/or subsequent restoration:					

- (12) Center-South One-Sixteenth corner of Section 12. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (12) Corner position established mid-point and on-line between the Center One-Quarter corner and the South One-Quarter corner of Section 12.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(12) DNR monument

4" Cedar N17E 16.35' (1/16S,BT)

5" Cedar S25E 14.22' (1/16S,BT)

8" Cedar S51W 9.45' (1/16S,BT)

7" Cedar N40W 12.02' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

50447

JEREMY J.
PIPP
PROFESSIONAL
SURVEYOR
No.
50447 Dalke

October 1, 2013

Signed by
Surveyor's Michigan License No.

For the Michigan Department of Natural Resources, For