

P.A. Of 1990 On 9/25, 19996
Menominee PLS
Chairman

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MENOMINEE
(County)

Located In:

Corner Code #

1. Public Land Survey

T37N R 25W

B13

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

SAME AS CORNER B-1 T36N-R25W

I, William Lenca, in a field survey on Sep. 09, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1847: Original Survey by James H. Mullett - B.T.'s - Hemlock, 10" - N67°E - 17 lks.; Hemlock, 10" - N70°W - 05 lks. All original evidence for this corner has been destroyed by logging activities and fire.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner was reestablished on line and proportionately between the Southwest Corner of Section 31 (A-13) and the South Quarter Corner of Section 32 (D-13), and is accepted as a careful and faithful reestablishment of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set 2" dia. Aluminum Pipe/3-1/4" dia. Alum cap stamped for corner location:

8" dia. Maple	N55°E	27.42 feet	Scr. NBT
8" dia. Maple	S85°E	42.64 feet	Scr. NBT
8" dia. Maple	S62°W	38.47 feet	Scr. NBT
7" dia. Maple	N67°W	5.36 feet	Scr. NBT
Metal Survey Sign Post	S26°W	1.5 feet	

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca
Surveyor's Michigan License No. 26461

Date

Sep. 24, 1996

RECEIVED FOR RECORD
96 OCT - 7 PM 3:27
PAGE # 373
BARBARA MORRISON
REGISTERED OF DEEDS
JANUARY 1996

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6			5		4			3		2	1
3												
4	7			8		9			10		11	12
5												
6	18			17		16			15		14	13
7												
8	19			20		21			22		23	24
9												
10	30			29		28			27		26	25
11												
12	31			32		33			34		35	36
13												

