

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee (County) Located In: Corner Code #
1. Public Land Survey
2. Property Controlling Section
3. Miscellaneous Property in Sec.
4. Lot No. , Recorded Plat
5. Private Claims

3/06/2014
Jeremy J. Pipp, in a field survey on 3/06/2014 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(05) Center-North One-Sixteenth corner of Section 29. Not set in original survey, no evidence of subsequent establishment.

(06) Northeast One-Sixteenth corner of Section 29. Not set in original survey, no evidence of subsequent establishment.

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(05) Corner position established mid-point and on-line between the Center One-Quarter corner and the North One-Quarter corner of Section 29.

(06) Corner position established at the intersection of the North and East One-Sixteenth lines of Section 29.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(05) DNR monument
8" B. Spruce N52E 8.30' (1/16S,BT)
8" B. Spruce S63E 4.94' (1/16S,BT)
9" B. Spruce S70W 5.47' (1/16S,BT)
5" B. Spruce N50W 17.48' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

Signed by Surveyor's Michigan License No. 50447

For the Michigan Department of Natural Resources

(06) DNR monument
10" Maple N55E 33.42' (1/16S,BT)
10" Cedar S29E 63.42' (1/16S,BT)
4" Tamarack S15W 35.27' (1/16S,BT)
5" W. Pine N40W 4.52' (1/16S,BT)

All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.



Date July 9, 2014

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number. Contains numerical data for each cell.