## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

1. Public Land Survey  T 40N R 26W J12 T R  2. Property Controlling S T R  in Section S T R  3. Miscellaneous S T R  Property in Sec. S T R  4. Lot No. Recorded Plat  5. Private Claims  7/01/2013AD  7/01/2013AD  Abat under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 to bow were in conformance with regulations and rules therefore as required in the current manual of survey survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 1 Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with 7 the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, 8 19 20 21 22 23 24 24 25 25 25 25 25 25 25 25 25 25 25 25 25	Menominee (County)	Located In:	Corner Code #	
2. Property Controlling S T R In Section S T R 3. Miscellaneous S T R Property in Sec. S T R  4. Lot No. , Recorded Plat 5. Private Claims  7/01/2013AD  7/01/2013AD  7/01/2013AD  ABC D E F G R I J K I M  ABC D E F G R I J K I M  The subsequence of Security of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with regulations and rules therefore as required in the current manual of survey on the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with restablished, monumented, recovered, found as expressed below:		T 40N R 26W	<del></del>	
4. Lot No. , Recorded Plat  5. Private Claims  7/01/2013AD  7/01/2013AD  7/01/2013AD  7/01/2013AD  A B C D E F G K I J K L M  7/01/2013AD  7/01/2013AD  A B C D E F G K I J K L M  7/01/2013AD  7/01/2013AD  7	in Section  3. Miscellaneous	S T R S T R S T R S T R		Register of Deeds Stamp & File Number
hat under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey nstructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 18 17 16 15 14 13 16 15 14 13 16 15 14 13 16 15 14 13 17 16 15 14 13 16 15 16 15 16 17 16 15 16 17 16 15 16 17 17 16 17 16 17 17 16 17 17 16 17 17 16 17 17 16 17 17 16 17 17 16 17 16 17 17 17 16 17 17 17 16 17 17 16 17 17 17 16 17 17 17 17 17 17 17 17 17 17 17 17 17	, , , , , , , , , , , , , , , , , , , ,	corded Plat		
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 shove were in conformance with regulations and rules therefore as required in the current manual of survey nstructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 18 17 16 15 14 13 16 15 16 15 16 15 16 15 16 15 16 15 16 15 16 17 16 15 16 16 15 16 15 16 15 16 15 16 15 16 15 16 15 16 15 16 15 16 15 16 16 15 16 16 15 16		7/01/20	13AD	2 - 5 - 4 - 3 - 2 - 1 - 1
	that under requirements of P.A. above were in conformance with a nstructions of the United States It. Court of Law and /or that the continues of the Michigan Board re-established, monumented, recovery NOTE: Not more than 2 corrections.	74, Michigan P.A. of 1970, the corner regulations and rules therefore as required pepartment of the Interior, Bureau of corner points mentioned in lines 3, 4 and of Land Surveyors or by a Decrement, found as expressed below:	r points mentioned in lines 1 and 2 ired in the current manual of survey Land Management or by a decree of a 5 above were in conformance with e of a Court of Law; established,	7

- (I12) Quarter corner common to Sections 34 and 35. 1852: Harvey Mellen, DS. Set Qr. Section post witnessed by Spruce 6 S46W 10 links (6.60'), Cedar 9 S82E 11 links (7.26').
- (J12) Center One-Quarter Corner of Section 35. Not set in original survey, no evidence of subsequent establishment.
- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (I12) No evidence of original survey. Corner position reestablished by single proportionate measurement between the Northwest corner and the Southwest corner of Section 35. Position is accepted as a careful and faithful REESTABLISHMENT of the position of the original corner.
- (J12) Corner position established at the intersection of the North-South and East-West One-Quarter lines of Section 35.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(I12) DNR monument 7" Cedar N52E 13.97' (1/4S,NBT) 4" Cedar S55E 8.36' (1/4S,NBT) 8" Cedar S53W 12.41' (1/4S,NBT) 6" Cedar N68W 25.74' (1/4S,NBT) All trees are blazed, scribed, painted, and signed. Measurements are to nail in side of tree, bearings are magnetic. A	(J12) DNR monument 7" Poplar N10E 25.74' (1/4S,BT) 4" Balsam S66E 14.23' (1/4S,BT) 4" Poplar S21W 15.85' (1/4S,BT) 5" Poplar N57W 6.20' (1/4S,BT) All trees are blazed, scribed, and painted of the same and painted of the same are to nail in
metal sign post was set North 1.5 feet.)	of tree, bearings are magnetic.
Signed by	JEREMY Date * August 08, 2013

Surveyor's Michigan License No.

PROFESSIONAL

1 50447 For the Michigan Department of Natural Resource