## SURVEY & REMONUMENTATION

FEB 0 6 1998

## **Montmorency County Remonumentation**

Liber 00012 Page 0253

## SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	3	0. 7-0. 7-4, III.O.II. 7 .A. 1	370		
Montmorency (County)	Located In: Albert Township	Corner Code =##	STATE OF MICHIGA MONTMORENCY COUN	ŤΥ	
Public Land Survey	T <u>29N</u> R <u>1E</u> T <u>29N</u> R <u>2E</u> T R	M-6 & A-6	Recorded & Filed 10-17-1997 11:41		
in Section S	T R		A. PANGAN-MCELRO REGISTER OF DEED!		
	T R		Register of Deeds Star	np & File Number	
4. Lot No, Recor	ded Plat		ABCDE	FGHIJKLW	
·			2 6 5	432	
do hereby certify that under requirent in lines 1 and 2 above were in conficurrent manual of survey instruction Management or by a decree of a Courabove were in conformance with the Court of Law; established, re-established	formance with regulations and rule is of the United Stales Department or of Law and/or that the corner point rules of the Michigan Board of Land	U, the corner points mentioned is therefore as required in the of the Interior, Bureau of Land its mentioned in lines 3, 4 and 5	4 - 7 - 8 - 5 - 6 - 18 - 17 - 1 7 8 - 19 - 20 - 2 9 10 20 20 20 20 20 20 20 20 20 20 20 20 20	9 10 11 12 13 14 13 14 13 14 13 14 13 14 13 14 13 14 15 15 14 15 15 14 15 1	
NOTE: Not more than 4 corner on this certificate.	s, all in the same town and ran	ge, may be recorded	11	3 34 35 36	
A. Description of original monu M-6 ½ corner for Section	ment and accessories and/or si	ubsequent restoration:	13		
N.E. & W. Cert L.C.R.C. Aug. Oct. 1973- Larry G. Beaur of Sur. not Re June 1978- Delmer E. Port Wit's mkd: (S Aug. 1978- Ronald R. Biscl Wit's mkd. Sam Oct. & Dec. 1986- Larry G 366, 367, 368 8	72- Norman C. Caldwell P.S of Sur. Rec. L. 1, Pgs. 21 7, 1972. Rec. L. 1, P. 26. S egard P.S. #18654, Fnd. ½" b c. er P.S. #15410, Fnd. ½" rod. 62° W 44.25' 9" Oak) (S 40° her P.S. #22482, Fnd. ½" rod e as recorded on Porter's su . Beauregard P.S. #18654, Fn & 369. Wit's mkd: (S 40° E 4 ng P.S. #25852, Fnd. Rec. ir	6-222. Wit's mkd: (S 60° Same wit's.  Foar & cap & wit's by Calc  in conc. Cert. of Sur. R  E 48.49' P. Pole).  ! in conc. No cap & two w  rvey.  d. ½" bar in conc. Cert.  8.50' P. Pole) (N 51° F	P E 38.2' 14" Oak) (N	60° E 33.1' 20" Oak P.Pole) it's mkd. Cert. P-Rec. L. 2, P. 455. 1, P. 233. Ows: L. 3, Pgs.	
B. Description of corner evid	dence found and/or method ap	plied in restoring or re	establishing corner:		
Fnd. ½" bar & P.S. cap #24	1600 (John F. Korr, Jr.) at	intersection of fence li	ne N. & W.		
Re-placed with 4" x 36" co	onc. mon. & Re-mon cap.				
M-6 ¼ corner for Section 1	 ccepted as the best availabl				
North 32.26' 6" x 6" Treat N 45° E 63.27' 20" Norway. S 25° W 121.33' P. Pole. S 40° E 49.06' P. Pole. N 60° E 33.1' 20" Oak Placed 60d penny spike, P.	ed post.(Placed P.K. nail & (P.K. nail & PS tag # 18654) " " " " " " " " " " " " " " " " " " "	18654) PEER GRC ) JUN <b>2 0</b> 9	OUP TO LICENSIDER	LARRY G. BEAUREGAR:D SURVEYOR NO. 18654	
signed by fung x	& Bearing and	Date/0	1/17/97	The ESSION PARTY AND THE PARTY	
Surveyor's Michigan License No.	.18654		FORM APPROVEO BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971		