

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Montmorency
(County)

Located In

Corner Code #

1. Public Land Survey T R
T R
2. Property Controlling in Section S T R
S T R
3. Miscellaneous Property in Section S 27 T 30 N R 02E 10
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on October 25 2010 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		6		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

10 - S 1/16 Cor. comm. to sec.'s 27 & 28, T30N,R02E

1977 - DNR Survey Map (Plan No. R-60-F) - Kenneth J. Ostling, P.S.#10068 - Set 5/8" x 40" bar midway and online between G10 and G11.
24" W. Oak N77°W 27.1'
23" R. Oak N20°W 65.8'

2001 - DNR Survey Map (Plan No. R-60-AY) - Carl T. Kiiskila, P.S.#33981 - Found and accepted 5/8" iron. No witnesses.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

10 - S 1/16 Cor. comm. to sec.'s 27 & 28, T30N,R02E

Found and accepted 5/8" iron by Ostling, added 5/8" plastic P.S.cap#33981. Corner falls 2' west of C/L N-S gravel road. Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10 - S 1/16 Cor. comm. to sec.'s 27 & 28, T30N,R02E

5/8"x 40" bar w/ plastic P.S. cap#33981

Wit: N42°E 82.45' to set N&T on SE side 21" R. Oak
N69°E 65.61' to fd. nail on S side 17&21" Twin W. Oak
N84°W 27.70' to fd. nail on N side 24" W. Oak
N27°W 65.95' to fd. nail on W side 20&27" Twin R. Oak
Set Blue Carsonite post w/ location tag 33' East



Carl T. Kiiskila

12-27-10

Surveyor's Michigan License No.: 33981