

**JAN 22 2001**

**Montmorency County Remonumentation**

Liber **00012** Page **0438**

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

MONTMORENCY

(County)

Located in:  
BRILEY TWP.

Corner Code #

1. Public Land Survey

T 30 N R 2E

C-4

2. Property Controlling  
in Section

S     

T      R     

3. Miscellaneous  
Property in Sec.

S     

T      R     

S     

T      R     

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

12-05-2000 10:05:34

TERESA WALKER  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat         

5. Private Claims         

I, DONALD E MARLATT, in a field survey on MAY 2000, 16X do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

**A. Description of original monument and accessories and/or subsequent restoration:**

C-4 1/4 COR. COMMON TO SECTIONS 7 & 8

G.L.O. COR. SET BY LEWIS CLASON IN APRIL 1840. Hd MAPLE 6" S31°E 53 L., Hd MAPLE 9"N63°W 19 L.

F. SMITH NOTES(P.S.#754) ROUSE 8/3/34 FOUND 24"STAKE WITH BOTTLE & STONES. SET 1/2"X2' BOLT (STAKE PROBABLY BY VALENTINE). N. END OF N. CURB N34°30'W 27.9', S. END OF S. CURB S39°W 28.4' ROUND STONE N33°30'E 46.85'(CO. RD. COMMISSION NOTES-NO DATE-N40°E 50'MONUMENT, S40°W 50' MON. G.G. SLATTERY P.E. MSHD SURVEY CREW CHIEF FOUND 1/2"IRON PIN IN CONC. 5/67. FOUND MONUMENT). MONUMENT BURIED 1'-RAISED WITH 5/8"IRON PIN, APPROXIMATELY 2' WEST OF OF CENTERLINE OF N & S ROADS AND IN CENTERLINE OF M-32 E & W. S55°E 85.88' 17"MAPLE, S30°E 48.96' 20"MAPLE, S50°W 47.62 TEL. POLE, N15°W96.93' P.POLE.

CLIFF LINDGREN P.S.#14098 OF MDOT FILED ACT 74 DATED FEB 14, 1996 & REC. IN L. 1, P. 521. FOUND 5/8"IRON PIN IN MON. BOX IN CENTERLINE OF M-32 & AND CENTERLINE OF BELT ROAD SOUTH & THORNTON ROAD NORTH. S50°W COR. FE. POST 50.49', S71°W 91.58' WOOD FE POST, N15°W 96.37' P.POLE(OLD HWY WIT.) N40°E 80.15' 19"ELM (AFTER CONSTRUCTION IN ORIGINAL POSITION).

**B. Description of corner evidence found and/or method applied in restoring or reestablishing co C-4 1/4 COR. COMMON TO SECTIONS 7 & 8.**

FOUND 5/8"PIN IN MONUMENT BOX AT INTERSECTION OF ROADS NORTH-SOUTH- EAST AND WEST.

N42°E 23"ELM 80.1' R.

N14°W P.POLE 96.35' R.

S50°W COR. FE. POST 50.63' R.

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

C-4 1/4 COR. COMMON TO SECTIONS 7 & 8.

PLACED REMON CAP ON 5/8" PIN IN MON. BOX

N42°E 23"ELM 80.1'

N14°W POWER POLE 96.35'

S50°W COR. FE. POST 50.63'

S26°W ROAD SIGN 52.06'

JUL 18 00

L.G.B.

WITNESSES ARE MARKED WITH 40 PENNY SPIKES AND PS TAGS# 18660.

APPROVED BY PEER GROUP ON JULY 18, 2000 AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER.

Signed by

Donald E Marlatt

Date

12/4/2000

Surveyor's Michigan License No.

18660