

SURVEY & REMONUMENTATION

JAN 22 2001

Montmorency County Remonumentation

Liber 00012 Page 0425

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MONTMORENCY

(County)

Located In: BRILEY Corner Code #

STATE OF MICHIGAN
MONTMORENCY COUNTY
Recorded & Filed

11-13-2000 13:33:50

TERESA WALKER
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey

T.30N. R. 2E E-6

2. Property Controlling
in Section

S. T. R.

3. Miscellaneous
Property in Sec.

S. T. R.

4. Lot No. , Recorded Plat

5. Private Claims

I, FREDERICK J. KING, in a field survey on APRIL 3, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-6 - 1/4 CORNER COMMON TO SECTIONS 16 & 17

June 1840 - Orig Post set by Lewis Clason, DS - (1)S53°E-45 lks(29.70') 8" Beech (2)N56°W-49 lks (32.34') 7" Beech-Pg. 45f
1941 - 2 1/2" Conc Mon Set by Frank Smith, PS#754 - (3)N45°W-50.0'-4" Conc Mkr. (4)S45°E-50.0'-4" Conc Mkr - (5)N52°W-213.8' 10" Birch
Info from L.G. Beauregard, PS#18654
April 1985 - Act 132 by D.E. Marlatt, PS#18660 - Rec. L. 3, Pg. 376 - Fnd 1/2" Rod - (7)N45°W-46.95'-P. Pole (8)N40°E-77.7'-P. Pole
Sept 1989 - Act 132 by F.J. King, PS#25852 - Rec. L. 3, Pg. 521 - Fnd Conc Mon In C.L.-C.L.Rds In Line Fnc to West.
June 1991 - Act 132 by D.E. Marlatt, PS#18660 - Rec. L. 3, Pg. 596 - Fnd Mon (7)N40°W-46.92'-P. Pole (8)N35°E-77.7'-14" Map
June 1996 - Act 132 by L.G. Beauregard, PS#18654 - (Surveyor for Scott Eng) Rec L.10004, Pgs 0358-0359-Exist Mon. (7)N45°W-46.93'-P.Pole (8)N35°E-77.32'-15" Map (9)N55°E-93.18'-Twin 8" Map (10)WEST-33.00'-I&C by King MICHIGAN

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-6 - 1/4 CORNER COMMON TO SECTIONS 16 & 17

Fnd: 5" Conc Mon (Rec as 2 1/2")

Witnesses - Fnd Rec. 7, 8, 9, & 10

THIS CORNER APPROVED BY COUNTY PEER REVIEW ON JULY 18, 2000, AS THE BEST AVAILABLE EVIDENCE OF THE RE-ESTABLISHMENT OF THE ORIGINAL CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-6 - 1/4 CORNER COMMON TO SECTIONS 16 & 17

Placed 3 1/4" Aluminum Montmorency County Re-Mon Cap on Fnd 5" Conc Mon.
Corner is ±1' W of C.L. N-S Grav Rd (Hossler Rd.) & ±3' N of C.L. Rd to E (Baker Rd.)
(Wit #8) - N35°E (R-N35°E & N40°E) - 77.36' - (R-77.32' & 77.7') - Set S&T above Fnd Spk - N-W side 16" Maple
(Wit #9) - N60°E (R-N55°E) 93.28' (R-93.18') - Set S&T above Fnd Spk - NW side Twin Maple
S20°E-81.06'-NW Cor of GTE Phone Box #1512-4-513
(Wit #10) - WEST - 33.02' (R-33.0') - Fnd I&C #25852 * N45°W - 49.87' (R-50.0') - Fnd 6" Conc Mon
(Wit #7) - N40°W - (R-N45°W) - 46.93' (R-46.93' & 46.95') - Set S&T above Fnd Spk - SW side Pwr Pole

Typical Wit Set = 16-D Spk & Plastic ID Tag #25852

APPROVED BY
PEER GROUP

Signed by

Frederick J. King

Date October 30, 2000

JUL 18 00

Surveyor's Michigan License No. 25852

J.L.B.