

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Montmorency</u> (County)	Located In:	Corner Code \neq
1. Public Land Survey	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S <u>13</u> T <u>31N</u> R <u>1E</u>	<u>15</u>
	S <u>13</u> T <u>31N</u> R <u>1E</u>	<u>16</u>
xxx Miscellaneous	S <u>13</u> T <u>31N</u> R <u>1E</u>	<u>13</u>
Property xxx Sec.	S <u>13</u> T <u>31N</u> R <u>1E</u>	<u>12</u>

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
 5. Private Claims _____

I, Carl R. Johnson, in a field survey on October 8, 19 90,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- 15 - Set corner by standard survey procedure for subdivision of a section.
 16 - Set corner by standard survey procedure for subdivision of a section.
 13 - Set corner by standard survey procedure for subdivision of a section.
 12 - Set corner by standard survey procedure for subdivision of a section.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

15 - W1/8 Cor. on S. Side Section 13
 Set 5/8" bar w/cap
 R. Pine 14" S75°E 27.65 ft
 R. Oak 15" N50°E 73.3 ft
 J. Pine 5" N15°W 39.8 ft

16 - E1/8 Corner on S. Side of Sec. 13
 Set 5/8" bar w/cap
 R. Pine 8" S68°E 13.2 ft
 R. Oak 6" S52°W 7.2 ft
 Maple 5" N70°W 22.1 ft

13 - Center of SE 1/4
 Set 5/8" bar w/cap
 R. Pine 8" S85°W 25.9 ft
 Maple 5" N20°E 11.9 ft
 Maple 4" S65°E 30.6 ft

12 - S1/8 Cor. on N-S 1/4 Line
 Set 5/8" bar w/cap
 R. Pine 18" S73°W 72.1 ft
 R. Pine 20" N8°W 19.4 ft
 J. Pine 6" S37°E 53.6 ft

Signed by Carl Johnson Date 1/14/91
 Surveyor's Michigan License No. 30083

