

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In: Montmorency (County)	Located In Vienna Twp.	Corner Code #
1. Public Land Survey	T 31N R 1E	H-4
2. Property Controlling in Section	T	
3. Miscellaneous Property in Section	T	
4. Lot No:	Recorded Plat:	
5. Private Claims:		

Register of Deeds Stamp & File Number

I, Carl T. Kiiskila, in a field survey on October 28, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													

A. Description of original monument and accessories and/or subsequent restoration:

H-4 C ¼ Corner Section 10, T31N,R1E

None

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

H-4 C ¼ Corner Section 10, T31N,R1E

Set stamped 2" dia. Aluminum cap on 5/8"x34" rebar per standard BLM procedure (intersection of ¼ lines). Found no other evidence to dispute the location for the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-4 C ¼ Corner Section 10, T31N,R1E

Stamped 2" dia. Aluminum cap on 5/8"x34" rebar.

Wit: N37°E 59.64' to set N&T on W side 3" W.Pine
S68°E 5.38' to set N&T on S side 3" W.Pine
N75°W 44.24' to set N&T on N side 10" R.Maple
N27°W 17.21' to set N&T on NE side 3" W.Pine
West 55.20' to fd. 1 ½"x 4.5' pipe.
East 57' to C/L dirt road running NE
Set Blue Carsonite Post w/location tag 1' North



Carl T. Kiiskila

11-23-10

Surveyor's Michigan License No.: 33981