

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Montmorency
(County)

Located In

Corner Code #

1. Public Land Survey T R
T R
2. Property Controlling
in Section S 3 T 31N R 1E 9
S T R
3. Miscellaneous
Property in Section S T R
S T R

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 27, 2011 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Instrument Liber Page
201100047924 1 754

201100047924
Filed for Record in
MONTMORENCY COUNTY, MI
TERESA WALKER, REGISTER OF DEEDS
08-18-2011 At 09:03:10 am.
LAND CORNER 14.00
Liber 1 Page 754 - 754

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4			3		2		1	
3													
4	7		8		9			10		11		12	
5													
6	18		17		16			15		14		13	
7													
8	19		20		21			22		23		24	
9													
10	30		29		28			27		26		25	
11													
12	31		32		33			34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

9 - CE 1/16 corner, section 3, T31N,R01E

None.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

9 - CE 1/16 corner, section 3, T31N,R01E

Set stamped 2" dia. aluminum cap on 5/8" x 34" rebar per standard BLM procedure. Found no other evidence to dispute the location for this corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

9 - CE 1/16 corner, section 3, T31N,R01E

2" dia. stamped aluminum cap on 5/8"x 34" rebar.

Witnesses:

N63°E 42.65' to set N&T on N side 12" J. Pine
S03°E 28.23' to set N&T on W side 13" J. Pine
S77°W 43.97' to set N&T on S side 10" J. Pine
N24°W 79.10' to set N&T on E side 9" J. Pine

Set blue Carsonite post w/ location tag 1' North.



Carl T. Kiiskila

8-11-11

Surveyor's Michigan License No.: 33981