

Liber 00012 Page 0111

Filing Requirement of Act 74, Mich. P.A. 1970

Montmorency
(County)

Located in: Vienna. TwoCorner Code =#

T 31N R 1E (A-6)

T _____ R _____

T _____ R _____

T R

T _____ R _____

2. Property Controlling in Section

S _____ T _____ R _____

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims

I, Larry G. Beauregard in a field survey on August, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A-6) GLO $\frac{1}{4}$ Sec. post set by John Mullett May 4, 1840.

Wits: Cedar 8" S 20° W 19 links

Maple 8" N 56° E 10 links

* Marcus Schaaf P.S. #3104 in 1930 found what he took to be corner marked by an old square stake.

No remaining evidence of corner. Wits: (Stump hole - Cedar roots S 20° W 19 links) (Stump hole - Cedar root N 56° E 10 links).

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A-6) Didn't find corner or witnesses. Set a 4" x 36" concrete monument with a 3" diam., Aluminum cap #18654 marked Montgomery County Re monumentation corner by single proportion method between Record section corners North and South.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A-6) $\frac{1}{4}$ corner common to Sections 18, T 31 N, R 1 E and 13, T 31 N, R 1 W

4" x 36" concrete monument and Remonumentation cap #18654. Accepted as a careful and faithful establishment of the position of the original corner.

6" Spruce S 40° E 36.22'

4" Spruce N 42° E 19.02'

10.5' East to H.W. North & South

12" Maple S 05° E 26.78'

10ⁿ Cedar N 50° W 73.80' (Ex. blaze)

Placed blaze, 20 penny spike & P.S. tag #18654 (typ)

Signed by

Date _____

Surveyor's Michigan License No. 18654

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26.
REVISED MAY 14.
REVISED JAN.