

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. 31 N. R. 2 E.		E-5; E-6
2. PROPERTY CONTROLL- ING IN SECTION 17, T. 31 N. R. 2 E.		7
3. MISCELLANEOUS PROPERTY IN SECTION_____, T._____, S., R._____, W.		
4. LOT NO._____, RECORDED PLAT_____		
5. PRIVATE CLAIMS_____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 28, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on\_\_\_\_\_, 19\_\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 5 Set corner at found 1" pipe which probably perpetuates M. Schaaf position and Frank Smith location as determined from Smith NBT's.
- 6 Set corner at location of several previous stakes, in accord with F. Smith NBT's and USBT stp. SW.
- 7 Set corner by standard survey procedure for subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-5	E-6	7
Set DNR mon. & cedar post	Set DNR mon. & cedar post	Set 5/8" bar w/RLS cap and
7" R. Oak S29°W 85.6	5" Cedar S49°E 22.6	cedar post
7" Spruce S86°W 34.7	5" Cedar S59°W 5.0	10" Cedar S60°W 36.0
		6" Cedar N24°W 4.8

SIGNED BY Kenneth J. Ostling

DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_

DATE

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_

DATE

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

MONTMORENCY COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET

