

# SURVEY & REMONUMENTATION

## Montmorency County Remonumentation

Liber 00012 Page 0136

APR 24 1995

### LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corner COMMISSION

Montmorency  
(County)

Located In:  
Montmorency Township

Corner Code #

STATE OF MICHIGAN  
MONTMORENCY COUNTY  
Recorded & Filed

11-10-1994 14:14:03

A. PANGAN-MCELROY  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T 32 N R 3 E A-6  
T R  
T R  
T R
2. Property Controlling S T R  
in Section S T R
3. Miscellaneous S T R  
Property in Sec. S T R

APPROVED BY  
PEER GROUP

AUG 05 94

*LLB*

4. Lot No. , Recorded Plat
5. Private Claims

I, Don Marlatt, in a field survey on November 8, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

#### A. Description of original monument and accessories and/or subsequent restoration:

- (A-6) W.  $\frac{1}{4}$  Cor. Sec. 18, T 32 N, R 3 E  
Original post set by Hiram Burnham July 1850, (Pine Post).  
18" Y. Pine N 50° W 31 links  
18" Y. Pine S 85° W 66 links  
Schaaf - DNR Survey - No Date.  
D. Porter - Recorded Act 74, L. 1, P. 397 on July 22, 1987.  
D. Marlatt - Survey in Sec. 13, T 32 N, R 3 E.

#### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- (A-6) W.  $\frac{1}{4}$  Cor. Sec. 18, T 32 N, R 3 E  
Found  $\frac{1}{2}$ " rod & cap #18660 in East track of trail road.  
Was established by Single Proportionate method on Town Line.  
6" J. Pine N 53° W 40.43'  
8" J. Pine North 2.08'  
12" Oak S 86° E 42.74'  
10" J. Pine S 29° W 30.62'  
No evidence of original corner.

Accepted as a careful and faithful establishment of the position of the corner.

#### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- (A-6) W.  $\frac{1}{4}$  Cor. Sec. 18, T 32 N, R 3 E  
Set concrete monument & Remonumentation Cap.  
6" J. Pine N 53° W 40.43'  
10" J. Pine S 29° W 30.62'  
12" Oak S 86° E 42.74'  
8" J. Pine North 2.08'

Witnesses marked with a 30 penny spike & I.D. tag #18660.

Signed by Donald E Marlatt

Date 11-9-1994

Surveyor's Michigan License No. 18660

