

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in  
MONTMORENCY

(County)

Located In:

Corner Code ##

1. Public Land Survey

T 32N R 4E

A-1, A-2

T R

A-3

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, CARL KIISKILA, in a field survey on AUGUST 22, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A-1

A-2

A-3

(NO EVIDENCE OF G.L.O. CORNER, B.T.'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O. LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-1

A-2

A-3

4-TWP. CORNER, FB PRESQUE ISLE CO. MON, FITS 1/2 HOLLOW 4'-5' TALL CEDAR STUB FOR USBT, N/REMAINS OF LOWER FACE, 10" CEDAR N77 W 33' (US= 6' CED N77 W 50LKS) & ALSO FB REMAINS OF POSS TAMARACK STP - USBT 519 E 39LKS(25.7'). OLD SINGLE STRAND SMOOTH WIRE ON OLD CEDAR POSTS TO N-E-W.

REESTABLISHED THE N1/4 COR OF SEC 6 PRORATED TO US-GLO RUNOUT(GEO. H. CANNON 1851) BETWEEN FD SW & NW COR'S OF SEC. 6.

FB 1/2" REROD BY D.MARLATT, FOR NW COR S-7, FITS U.S. B.T. STUMP TO NW (US= Y.PINE 18, N57 W 2.6'), FB LOWER FACE & NOTCH ON PINE STP. SL'Y EDGE OF CONIFER SWAMP IS 200'+/- NORTH. SMOOTH WIRE RUNS N & S UNDER OLD CEDAR POSTS. SE COR S-1, T32N-R3E, SET DNR MON IS N01°28'09"W, 232.94'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-1

A-2

A-3

FOUND PRESQUE ISLE CO. MON & CEDAR POST. SET CARSONITE POST 6" SPRUCE S88°W 10.05' 16" CEDAR N11°W 33.61' 5" SPRUCE N84°E 35.93' 5" SPRUCE S07°W 29.29'

SET 1" x 36" IRON PIPE W/ALUMN DNR CAP & CARSONITE POST. 4" CEDAR S11°W 5.54' 5" CEDAR S60°E 13.41' 7" CEDAR WEST 9.04' TAMARACK N10°W 11.83' E1/4 COR SEC 1, T32N-R3E, SET DNR MON N01°28'09"W 462.40'

SET DNR MON & CEDAR POST W/LOCATION TAG. 11" Y.PINE STP N57°W 2.6' 11" W.PINE N53°E 13.31' 19" W.PINE S07°E 10.06' 14" MAPLE(CLP 5) S51°W 11.25' 19" CEDAR N70°W 3.29' 1" WIT BY OTHERS 1" US GLO WIT.

COR AT SOUTH EDGE OF E-W OPENING THRU SWAMP. SMOOTH WIRE TO E & W.



Signed by Carl T. Kiiskila

Date 2-27-97

Surveyor's Michigan License No. 33981