

1994 NEWAYGO COUNTY REMONUMENTATION PROJECT

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

VOL 001 PAGE 132

For corners in

<u>Newaygo</u> (County)	Located In:	Corner Code #/
1. Public Land Survey	T 15N R 12W	E-5
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

NEWAYGO COUNTY
REGISTER OF DEEDS
MARLENE TOOGOOD

'95 MAR 14 PM 3 58

Marlene Toogood

Register of Deeds Stamp & File Number

I, Norman L. Ochs, in a field survey on September 19, 1994
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

NW Cor., Section 16, Monroe Twp., Newaygo County MI

A. Description of original monument and accessories and/or subsequent restoration:

GLO John Hodgson 1838 Delos G. Anderson (Co. Surveyor)
10" Tamarack N24°W 34 lks (22.44') #1 Book A Pg's 207 & 208 and Book # unknown#138.
9" Tamarack S34°E 47 lks (31.02') #2 August 3 to 5, 1897
12" Hemlock S81°E (19.14') 29 lks.


Lyle S. Shepherd RLS #503
Field Book 25, Pg. 22
Arpil 8, 1913
Measured 2640 ft. from NW Cor. to N-1/4 Cor.
Sec. 16 and measured 2640 ft. from NW
Cor. to W-1/4 cor. Sec. 16.
One old bearing tree found. Measured 40.41½
chains (2667.39 ft) from NE cor. to N-1/4
cor. Sec. 17. Measured 2666.52 ft. from NW
cor. to N-1/4 cor. Sec. 16.
(See reverse)--

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner position disturbed by old road bed.
Found remains of Hemlock stump (accessory #3) and set corner N81°W 19.14 ft. from
center of stump. I measured a distance to the N-1/4 corner of Sec. 17 of 2667.10
ft. and a distance to the E-1/4 corner of Sec. 17 of 2640.62 ft. Both distances
being in harmony with surveyors Anderson and Shepherd.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Newaygo Co. Harrison Monument* and is accepted as a careful and faithful
perpetuation of the original corner. *4" dia. cast iron 20" long
7" Maple S44°W 20.67' (60 d. spike in NW side). NOTE: Blazed all trees.
9" B. Oak S14°W 53.71' (60 d. spike in W side).
10" Maple S20°E 35.11' (60 d. spike in E side).
7" R. Pine S89°E 47.63' (60 d. spike in S. side).
U.S.F.S. plantation marker is 1.0' North and 3.5' West.



Signed by Norman L. Ochs Date September 29, 1994
Surveyor's Michigan License No. 22439
Approved by Peer Review Group on October 19, 1994. FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
Norman L. Ochs County Representative REVISED MAY 14, 1975
REVISED JAN., 1983

SURVEY &
REMONUMENTATION

DEC 4 / 2000

SECTION

A. cont.

Ralph A. Smith RLS #3421

7-17-51 Book 88, Pg. 2

12" Hemlock S81°E 19.14' (OBT) #3

Measured 2667.39 ft. from the NE cor.

to N-1/4 cor. Sec. 17 and measured

2630.76 ft. from the NW cor. to the N-1/4

cor. of Sec. 16.

NCRC

10" Tamarack N24°W 22.4' #1

9" Tamarack S34°E 31.0' #2

12" Hemlock S81°E 19.1' #3

SURVEY &
REMONUMENTATION

DEC 07 2000

SECTION