

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Ogemaw

(County)

Located In

Corner Code #

1. Public Land Survey

T

R

2. Property Controlling
in Section

S 1

T

21N

R

2E

4

S 1

T

21N

R

2E

12

3. Miscellaneous
Property in Section

S

T

R

S

T

R

Register of Deeds Stamp & File Number

4. Lot No:

Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 16, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

4- This corner position was not established during the original Government survey.

12- This corner position was not established during the original Government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

4- Set the Northwest corner of the Southeast quarter of the Northwest quarter of section 1 as per B.L.M. instructions for the subdivision of a section.

12- Set the Northwest corner of the Southwest quarter of the Southeast quarter of section 1 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

4- Set 5/8" X 32" rerod with P.S. Cap #33981

Wit: Set nail and tag SW side of a 14" Pin Oak S06°E 9.92'
Set nail and tag W side of a 10" Pin Oak S33°W 29.41'
Set nail and tag N side of a 12" Pin Oak S88°W 62.78'
Set nail and tag SE side of a 10" Pin Oak S88°E 62.78'
Centerline of 2 track N55°E 25'±

12- Set 5/8" X 32" rerod with P.S. cap #33981

Wit: Set nail and tag S side of a 7" White Pine S79°W 11.75'
Set nail and tag N Side of a 4" White Pine N53°W 8.50'
Set nail and tag SE side of a 9" Maple N59°E 36.11'
Set nail and tag S side of a 6" Maple clump N37°E 76.21'
Centerline of road S 65°W 28'±

Signed by:

Carl T. Kiiskila

Date:

12/19/07

Surveyor's Michigan License No.:

33981

