

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Ogemaw
(County)

Located In

Corner Code #

1. Public Land Survey T 21N R 2E L-2
T R
2. Property Controlling in Section S T R
S 1 T 21N R 2E 8
3. Miscellaneous Property in Section S T R
S T R

Register of Deeds Stamp & File Number

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on July 24, 2007 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

L-2 This corner position was not established during the original Government survey.

8 - This corner position was not established during the original Government survey.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

L-2 Set the center of section 1 at the intersection of the North-South and East West ¼ lines.

8 - Set the Northwest corner of the Northeast quarter of the Southwest quarter of section 1 as per B.L.M. instructions for the subdivision of a section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-2 Set 5/8" X 32" rered with P.S. Cap #33981

Wit: Set nail and tag SE. side of a 10" W. Pine S52°W 20.06'
Set nail and tag NE. side of a 24" B. Oak S35°E 20.77'
Set nail and tag E. side of a 6" J. Pine N2°E 68.05'
Set nail and tag W. side of a 3" R. Pine N13°W 80.93'
Center East-West road North 40'

8 - Set 5/8" X 32" rered with P.S. Cap #33981

Wit: Set nail and tag SE. Side of a 4' R. Oak S28°W 46.38'
Set nail and tag NE side of a 4" R. Pine S26°E 32.90'
Set nail and tag SW side of a 17" W. Pine N11°W 97.62'
Set nail and tag SE side of a 15" R. Oak N18°E 66.98'
Center East-West road North 15'

Signed by:

Carl T. Kiiskila

Date:

12/19/07

Surveyor's Michigan License No.:

33981

