

SURVEY & REMONUMENTATION

APR 24 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

L. 4 Pg. 44

For corners in

OSCODA

(County)

Located in:

DIG CREEK TWP

Corner Code #

H-7

STATE OF MICHIGAN
OSCODA COUNTY
FILED

15 NOV 94 11:10 A.M.

PATSY J. PETERS
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey

T 26N R 2E

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

APPROVED

County Remonumentation
Peer Review Group

NOV 94

I, FREDERICK J. KING

in a field survey on October 21

19 94

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-7 1/4 CORNER COMMON TO SECTIONS 15 & 22

July 1839 - Original Post set by Lewis Clason, D.S. - - - - - N28½E - Aspen - 9.24' (14 lks)
On File - Reg of Deeds S40W - Aspen - 12.54' (19 lks)
1935 - USGLO Mon set by Guy R. Veal, US Cad Eng - Set by Prop Meas - - S46½E - Poplar - 61.71' (93½ lks)
No Evidence of Orig Cor Fnd - On File - Reg of Deeds N79W - Poplar - 43.65' (66 lks)
Sept 1940 - GLO Mon Fnd by George D. Henning, RLS - No Witnesses - Rec Bk T26N-R2E
Mar 1976 - Cor used by N.C. Caldwell, RLS - No Cor Description - No Witnesses - Act 132 Rec L.2 Pg 325-326
NO ACT 74 FOUND RECORDED FOR THIS CORNER

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

10-21-94 - Found Rec USGLO Monument - - - - - South - 1.75' - Face of USFS Post
Wouldn't Dip - Set Iron & Area is now all open field -
ID Cap on S Side of Mon. No 1839 or 1935 Witnesses Found

This Corner was approved by the Oscoda County Peer Review Comm. as a Careful and Faithful Establishment of the Position of the Corner on November 1, 1994.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10-21-94 - Record USGLO Monument in Line with Fences N-S-E
With Iron & ID Cap #25852 on S. Side
N5E - 109.55' - Set Tag in E sd of 10" Birch
East - 21.83' - Set Tag in N Face of Fnc Post
South - 1.75' - Face of USFS Post
South - 19.92' - N Face of Grader Blade used as Fnc Post
(Painted Top of Grader Blade Red)
S80W - 74.12' - Set Tag in N sd of 10" Spruce

NOTE: Witness BTs were marked with Db1 Headed Nails with I.D. Tag #25852

Signed by

Frederick J. King

Date 11-4-94

Surveyor's Michigan License No. 25852

