SURVEY & REMONUMENTATION

APR 2 4 1995		
COMMISSION For corners in	LAND CORNER RECORDATION Filing Requirement of Act 74,	
in Section S _ 3. Miscellaneous S _	Located In: Corner Code = Big Creek Twp. T _26N R _2E	STATE OF HICHIGAN OSCODA COUNTY FILED
1. Larry G. Beauregardin a find of hereby certify that under requirement in lines 1 and 2 above were in conformangement or by a decree of a Court of above were in conformance with the ru Court of Law; established, re-estable expressed below: NOTE: Not more than 4 corners, on this certificate. A. Description of original monum (I-6) who displays the section post set whits: 8" B. Oak S 89½°	E 38 links 8" Y. Pine N	2 6 5 4 3 2 3 3 4 7 8 9 10 11 12 12 13 13 11 18 12 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 13 11 18 18 18 18 18 18 18 18 18 18 18 18
Clarence Seeley in 1914 S 2010 W 681 links M B T	set 1½" well pipe at stake. Wits: (8" `\	B.Oak S 4¼° W 54½ links N.B.T.) (8⊓ B. Oak

Guy R. Veal in 1935 found no remaining evidence of original post or B.T.s. Set brass tablet $3\frac{1}{2}$ " diam, 3" stem in conc. mon. 24" long, 6" diam., 30" in ground with top marked Secs. 14 & 15. Gov't Deputy Surveyor. Dependent

Resurvey of T26N, R2E. Local B.T.: (8" B.Oak S 2½° W 57 links) (8" B. Oak S 20½° W 71 links). Wits: (5" J.Pine N 8° E 152 links). Norman C. Caldwell P.S. #12018 in 1968–1981 found $1\frac{1}{2}$ " pipe from U.S. GLO N.B.T.s, position now preserved by M.S.H.

mon. box 2.06' South of C/L. Wits: (14" Oak N 07° W 93.7') (8" J.Pine N 07° E 100.6') (9" Oak N 25° E 106.1') (North 75' conc.plat mon.). Larry G. Beauregard P.S. #18654 in 1970-present found P.K. nail in 2" pipe in mon. box (R). Recorded L.193, P.1574

Wits: (P.Pole S 50°E 63.65'-P.K. mail & P.S. tag #18654) (P.Pole N 55° E 68.73'-P.K. mail & P.S. tag #18654) (P.Pole N 45° W 96.03' - P.K. mail & P.S. tag #18654) (North 52.58' corner fence post). Clifford Lindgren P.S. #14098 in 1993 found $\frac{1}{2}$ " pipe 2.06' right of station 1510 + 04.96. LCRC recorded L. 3, P. 24

Wits: (14" Oak N 87° W 93.65') (8" J.Pine N 87° E 188.62') (9" Oak N 25° E 186.18') Fnd. 6" pipe 2.8' S. of M-7 C/L & C/L of Mishler Rd. South. Witnessed corner in 1992. Fnd 2" pipe in mon. box after construction at correct location. 2" pipe in mon. box 1.5' South of M-72 C/L. Wits: (Ex. nail in G. Pole N 45° W 96.07') (North 68.46' top center R/W marker)(Ex. mail in T. Pole N 55° E 68.76'). Ex. P.K. mail in P.Pole S 45° E 63.62'.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- (I-6) Found 2" pipe in mon. box 2.06' S. of M-72 C/L. Placed $\frac{1}{2}$ " x 12" re-bar & cap inside same.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- (I-6) 1/4 corner common to Secs. 14 & 15, T26N, R2E

2" pipe in mon. box 2.06' S of M-72 C/L. Placed $\frac{1}{2}$ " x 12" re-bar & cap inside same and is accepted as a careful and faithful reestablishment of the position of the original corner.

R/W marker S. face conc. North 68.27' Anchor Pole N 45° W 96.03' (Placed P.K. nail & P.S. tag #18654) P.Pole S 40° W 63.59' (Placed P.K. nail & P.S. tag #18654) T. Pole N 55°E 68.73' (Placed P.K. nail & P.S. tag #18654)

Surveyor's Michigan License No. ___18654

REVISED MAY 14, 1975 REVISEO JAN., 1983