CECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

	Filing Requireme	nt of Act 74, Mich. P.A. 19	070
For corners in			Liber 5 pg. 90
Ossada	Located In:	Corner Code #	STATE OF HICHIGAN
Oscoda	Located in:	Comer Code #	OSCODA COUNTY
(County)			FILED
1. Public Land Survey	T <u>27N</u> R <u>_2E</u> TR TR		9 AUG 2000 3:31:29 PM
	TR		PATSY J. PETERS
Property Controlling in Section	STR STR		REGISTER OF DEEDS
3. Miscellaneous	STR		m 14 cm 1 ot B PH- Number
Property in Sec.	STR		Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat			
5. Private Claims	-		2 -6 - 5 - 4 - 3 - 2 - 1
•			3
I Marvin F Myers in a field surv	ey on <u>June 16, 2000</u> do hereby state ti	hat under requirements of P.A. 74.	4 -7 - 8 - 9 - 10 - 11 - 12 -
	r points mentioned in lines 1 and 2		5
regulations and rules therefore as required in the current manual of survey instructions of the United States 6			
Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the			
	1 and 5 above were in conformance w		8 19 20 21 23 24
of Land Surveyors or by a Decree	of a Court of Law; established, re-est	ablished, monumented, recovered,	9
found as expressed below:			10 30 -29 -28 -27 -26 -25
	rners, all in the same town and	I range, may be recorded	11 22 22 23 24 35 36
on this certificate.			12 31 32 33 34 35 36
A. Description of original monument and accessories and/or subsequent restoration. Comer common to Sections 7, 8, 17, and 18, T27N, R2E			
G.L.O.	John R. Randall, Cou	nty Surveyor 1885	Marcus Schaaf, Surveyor, Circa 1930's
William R. Coon, D.S. 1839	Mon: Remarked come	_	cus Schaff's Index, no notes were
Mon: post		by following U.S. bearing trees foun	•
Wit: 4" Spruce Pine N23°E 78 1/2 lii		, ,	Mon: Found of established, and replaced.
4" Dwarf Oak S60°E 3.14 chain	-	/	
	4" Dwarf Oak \$3	3°W 93 1/2 links	
Norman C. Caldwell, P.S. #12018 1967 Survey's			
Mon: Set 6" x 6" concrete point in position indicated on Elmer Township Cemetery, but could not find any evidence of 1885 comer by J. Randall found the original			
Gov. Bt's of 1839 and established 2	new BT's, It's assumed that this come	er was in existence and the boundary	y was laid out from the same. In the 1930's the
•	ain lines in the area & show BT's for a	corner at this location. None of the	New BT's are now in existence and the corner has
been established as stated.		1000 O	and I I I M. Dansey
Wit:8" Jack Pine S45°W 14.8'	12" Jack Pine N55°E 27.6"	1968 Consumers Power of	•
10" Jack Pine N70°W 50.8' 26"	Norway Pine S15°E 123.5'	Mon – Found Square Cor Wit: 86' N. of Centerline	
12" Jack Pine N15°W 59.0"		Wit. 60 N. Of Centerine	APPROVED
Norman C. Caldwell, P.S. #12018			a see of the see of th
L.C.R.C Liber 1 Page 115, 1973 Mon: replaced monument with Stand	dard County Corner	_	County Remonumentation
	" Jack Pine N55°E 27.6'; 10" Jack Pine	N70°W 50.8': 26" Norway Pine S1	5°E 123.5' COF Review (Proup
	ed D.N.R. marker post alongside	2	NCC
in depth incline the part has	or continuous poor annual		5°E 123.5' Poer Review Group NCC 27 JULY 00
B. Description of corner ev	vidence found and/or method a	applied in restoring or reesta	ablishing corner:
Corner common to Sections 7, 8,		-	
Found Standard County Monument;	found red top post; found 26" Norway	Pine S15°E 123.5; found stump of	8" J. Pine S45°W 14.8; found stump of 12" J. Pine
N55°E 27.6. Accepted Standard Co	unty Monument as the best available e	vidence of the Position of the Origin	al Government Corner.
		established to perpetuate lo	cating the position of the corner:
Corner common to Sections 7, 8,			MILLE OF MICHAEL
N55"E 27.6. Accepted Standard County Monument as the best available evidence of the Position of the Original Government Corner. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Corner common to Sections 7, 8, 17, and 18, T27N, R2E Mon – Standard County Corner Monument. Wit: Nail & tag SW side 21" Oak S58"W 28.99 Nail & tag S. side 12" Oak N68"E 42.73 Nail & tag S. side 20" J. Pine S46"E 35.83 Nail & tag E. side 18" J. Pine North 59.44 Signed by Date July 10, 2009 The Sign National Surveyor's Michigan License No. 31600 Surveyor's Michigan License No. 31600 FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL 31.197			
	•	de 18" J. Pine North 59.44	MARVIN E.
Nail & tag S. side 20" J. Pir.	EU-OLE JULOU MAII A LAYE. SI	US IO 9, FING BURI DOM	F/ MYERS
122	-02		PROFESSIONAL O
Signed by	54 / Mys	Dat	e July 10, 2000可人 SURVEYOR 人
Summaria Michigan Licana No. 31600			
Surveyor's Michigan License N	J. <u>31000</u>		Million Promising States
		•	WHITE THE STORY OF
		FORM APPROVED BY MIC	REVISED MAY 14, 197:
			REVISED JAN., 198: REVISED OCT., 199: