

OCT 0 8 1997

COMMISSION	LAND CORNER RECORDAT	ION CERTIFICATE LIBER 4 Pg. 23
For corners in	Filing Requirement of Act 74	4, Mich. P.A. 1970 STATE OF HICHIGAN
00000		OSCODA COUNTY
OSCODA Locate (County) COMIN	ed In: Corner Code # S TWP.	FILED
1. Public Land Survey	T <u>27N</u> R <u>3E 1-13 </u>	3 OCT 97 12:42 P.M.
	TR TR	PATSY J. PETERS REGISTER OF DEEDS
2. Property Controlling S in Section S	TR TR	
3. Miscellaneous S	TR TR	
Property in Sec. S	IR	Register of Deeds Stamp & File Number
4. Lot No. Recorded Plat		
5. Private Claims		A B C D E F G H I J K t
		2 - 6 - 5 - 4 - 3 - 2 - 1 -
1 EDEDEDICK 1 KING :	4	3
i adamamanta or i 'v' i 4' Michigali E'V' Ol I	d survey on <u>July 7</u> , 19 <u>97</u> do herel 970, the comer points mentioned in lines 1 an	(al C) a feature 1
Comornance with regulations and rules merel	fore as required in the current manual of survey eau of Land Management or by a decree of a C	inctructions of the District Inches
triat the corner points mentioned in lines 3, 4	and 5 above were in conformance with the nut	an of the Michigan
recovered, found as expressed below:	of a Court of Law; established, re-establish	ed, monumented,
NOTE: Not more than 2 comes all in the		8 -19 -20 -21 -22 -23 -24
on this certificate.	ne same town and range, may be recorded	9 10 30 29 28 27 26 25
, in the second second	unty Remonumentation Recr. Review Group discressories and/or subsequent restored	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
Co	unty Remonumentation 2051	12 - 31 - 32 - 33 - 34 - 35 - 36 - 36 - 36 - 36 - 36 - 36 - 36
A. Description of original monument ar I-13 - CORNER COMMON TO SECTIONS	Peer Review Group 30 accessories and/or subsequent restor	ation:
		(23.76') - 7" Pine - N83°W - 31 lks (20.46') -6" Pine
Sept 1930 - GLO ReSurvey by G.R.	Veal - Cor ReEstablished by Randa	ill in 1884 from Orig. BTs - On File @ Reg of Deeds Po
Fnd 1½" Bar with 4"x4 Cor I-1 (26-3) is 12.	54' EAST N83°W - 31	ur with 6"x24" Conc Mon & Brass Cap lks (20.46°) - Fnd Stump - Orig BT
New Wit Marked - N59⅓	010 - 163°W 0N-123 lks (81.18') - 10" j Pine) lks(138.60') - Fnd Stump - by Randall - N40 ⁰ E -57 lks (37.62') - 6" J Pine
N414	$^{ m OE}$ - 41 1ks (27.06') - Fnc Cor Pos	st - Fnc N & E
Aug 1967 - Act 132 by N.C. Caldw	ell, PS #12018 - FNd GLU Mon - Ra ell, PS #12018 - No Cor Desc - No	nised with R.R. Spike - No Wit - On File @ Reg of Deed
June 1977 - Act 132 by N.C. Caldw	ell, PS #12018 - No Cor Desc - No) Wit - Rec L. 2. Pg. 454
July 1979 - Act 132 by N.C. Caldw Aug 1979 - Act 132 by N.C. Caldw	ell, PS #12018 - No Cor Desc - No ell, PS #12018 - No Cor Desc - No) Wit - Rec L'. 3, Pg 100-101
Sept 1979 - Act 74 by N.C. Caldwe	11. PS #12018 - Fnd GLO Mon - Rai	ised with Bar & Can - N730W - 47.6' - 10" '1 Pine
N69°E - 77.0' - 10" 'J	Pine EAST - 12.8' - Cor I-1 (26	3-3)
I-13 - CORNER COMMON TO SECTION	Tound and/or method applied in r S 34 & 35	restoring or reestablishing corner:
FOUND R.R. SPIKE IN MON B		. Rd. (Abbe Road) - Road Construction destroyed Rec (
	EAST - 12.63' (M) - Four	nd GLO Mon & Cap in Mon Box on East edge of B.T.
This Corner Approved by County Pe	er Review on July 11, 1997, as a	perpetuation of the Original Government Corner.
C. Description of monument for co I-13 - CORNER COMMON TO SECTIONS	rner and accessories established 34 & 35	to perpetuate locating the position of the corner:
**************************************	- Over GLO Mon - In Mon Box - ±1.	W of C.L. of N-S B.T. Rd (Abbe Rd)
N40°E - 56.82' - Set S&T	on SE side of Utility Pole	c. in C.L. of gravel road E (Cherry Creek Rd.)
\$35°E - 55.72' - Set \$&T	on W side of USFS Red Top Post	-1
WEST - 34.87' - Set S&T N30 ⁰ W - 50.92' - Set S&T	on S side of 12" J. Pine (Fnd Blz on NE side of 12" Oak	2)
		LO Mon in Mon Box @ Cor I-1 (26-3)

Surveyor's Michigan License No._