

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oscoda

(County)

Located In:

Corner Code #

1. Public Land Survey

T 27N R 4E

I-4-W, I-5-W

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

Liber 4 pg. 77

STATE OF MICHIGAN
OSCODA COUNTY
FILED

2 AUG 95 9:41 A.M.

PATSY J. PETERS
Register of Deeds & File Number
REGISTER OF DEEDS

I, David B. Babbitt, in a field survey on Sept. 12, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-4-W; Not previously Established

I-5-W; Not previously Established

APPROVED

County Remonumentation
Peer Review Group

NCC/31-~~406~~ 95
JULY

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-4-W; Set monument on the section line common to sections 10 and 11 at a point 471.70 Ft. North of the $\frac{1}{4}$ corner common to sections 10 & 11 (I-4) as a witness monument to said $\frac{1}{4}$ corner which falls in Shamrock Lake. This monument is Approx. 50 feet north of the north shore of Shamrock Lake.

I-5-W; Set monument on the section line common to sections 14 and 15 at a point 1211.18 Ft. South of the section corner common to sections 10, 11, 14 & 15 (I-5) as a witness monument to said section corner which falls in Shamrock Lake. This monument is Approx. 45 feet South of the South Easterly Shore of Shamrock Lake.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-4-W; Set 1" pipe with Oscoda County brass cap.

8" Oak - N35E - 48.65'

11" Oak - S22E - 39.04'

18" Oak - S75W - 34.62'

12" Oak - N41W - 36.04'

I-5-W; Set 1" pipe with Oscoda county brass cap.

18" N. Pine - N18E - 55.11'

21" Oak - S42E - 50.51'

12" Cedar - S54W - 71.93'

21" N. Pine - S66W - 26.99'

All bearings shown are actual compass readings and measurements are to a 3" nail with plastic cap in the side of each witness tree at the top of the root crown.

Signed by

David B. Babbitt

Date Sept. 26, 1994

Surveyor's Michigan License No. 21558