

**OTSEGO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE**
Filing Requirement of Act 74, Mich. P.A. 1970
South Charlton Township

For corners in

Otsego

(County)

Located In:

Corner Code #

1. Public Land Survey

T 29N R 1W

E-6

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

I, Carl T. Kiiskila, in a field survey on September 6, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

E-6 1856 GLO H. Mellen set quarter section post.

Wit: Sp. Pine 8" N7°E 60

Sp. Pine 8" S52°W 355

County Survey Book 3, Page 504, (1965) shows a ½" bar set by Stanley Thorsen on East slope railroad grade for the corner.

Wit: Oak 10" N25°W 53.8'

S. Pine 12" N45°E 22.3'

S. Pine 10" S58°W 14.8'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-6 Found a ½" x 48" bar on the East slope of an old railroad grade fitting a single proportion position.

Wit J. Pine 14" S50°W 14.8' dead

J. Pine 18" N54°E 22.93'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-6 Set an Otsego County Monument in place of found ½" bar is accepted as careful and faithful re-establishment of the corner position.

Drove the ½" x 48" bar below grade on the East side of monument.

Wit Set nail & tag 18" J. Pine N54°E 22.93'

Set nail & tag 12" R. Pine S48°E 26.12'

Set nail & tag 6" Oak S05°W 11.00'

Set nail & tag 18" J. Pine N60°W 22.02'

Centerline N-S road East 91'

Signed by

Carl T. Kiiskila

Date

10/8/07

Surveyor's Michigan License No. 33981