APR 2 5 1995

OTSEGO COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

LIBEROOO4 PAGEO 16

COMMISSION

Filing Requirement of Act 74, Mich. P.A. 1970 ALSO ACT 345, PA 1990 Corner Code ## Located in: OTSEGO COUNTY MICHIGAN RECEIVED FOR RECORD M.C. between___ T 29N R 2W 1. Public Land Survey K-3 & 11-2 ____ R ____ 94 DEC 14 PM 4: 02 B EVELYN M. PRATT CLERK / REGISTER OF DEEDS R 2. Property Controlling R S in Section Register of Deeds Stamp & File Number Miscellaneous R s Property in Sec. ___ , Recorded Plat _ 4 Lot No. 5. Private Claims _ 19 94 November 7 James L. Schwandt in a field survey on . do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below: NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate. A. Description of original monument and accessories and/or subsequent restoration; Carl I. Robinson #16390, 1989 G.L.O. Harvey Mellen, 1856 Set O.C.M. 8.5' East of East Shore Set Post 30" W. Pine N83°E 25 Lks. Big Bass Lake 8" R. Pine N21°E 17.78'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found O.C.M. set on line between J-3 and K-3 per C.I. Robinson survey dated 4-10-89. Robinson's L.C.R.C., Liber 3, Page 28, states no prior restoration or perpetuation.

24" W. Pine N47°E 37.12' 12" R. Pine S6°E 18.33" 10" R. Pine N41°W 27.99'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M.C. between K-3 & 11-2

Found O.C.M. is accepted as a careful and faithful re-establishment of the position of the original corner. Corner set on line between J-3 and K-3 per Chambinson Survey of 4-10-89.

10" R. Pine S45°W 27.99' Ed. Nail OTSEG

10" R. Pine S45°W 27.99' Fd. Nail 12" R. Pine S73"E 18.33' Fd. Nail 8" R. Pine N80°E 17.78' Fd. Nail 24" W. Pine N51°E 37.12' Fd. Nail STATE OF MICHIGA JAMES L. SCHWANDT PROFESSIONAL SURVEYOR No. 26468 OFESSIONA

OTSEGO COUNTY REMONUMENTATION

Approved by the County Survey Peer Group, pursuant to Act 345, PA 1980.
DEC.13, 1994

Date

18" Y. Pine \$10°E 34 Lks.

December 7, 1994

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 26, 1971 REVISEO MAY 14, 1915 REVISEO JAN., 1983