

OTSEGO COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Located In Charlton Corner Code #  
Otsego Twp. North  
(County)

1. Public Land Survey	T	31N	R	1W	K-3
	T		R		
2. Property Controlling in Section	S	T		R	
	S	T		R	
3. Miscellaneous Property in Section	S	T		R	
	S	T		R	

4. Lot No: Recorded Plat:

5. Private Claims:

I, Carl T. Kiiskila, in a field survey on June 19, 2013 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

K-3 Corner common to Sections 1,2,11&12, T31N, R01W

1850 – GLO – Austin Burt- Set post corner of sec. 1,2,  
11& 12  
Beech 22 S22E 21  
Beech 6 N49W 10

1940 – Co. Surveyor Bk. 2, Pg. 378  
G.F. DeLaMater P.S. #2674  
found both Gov'ts B's and P's  
Set ½"x36" bar in corner  
W. Pine 2 S17°W 72.2  
W. Pine stump 40 S20°E 46.9

1981- Liber 2, page 213 Danny M. Bongiovanni P.S.  
#24586 found a ½" iron bar and both of  
DeLaMater's witnesses.  
Pine stump w/blaze S 20°E 46.9'  
24" W. Pine S17°W 72.2'  
5" W. Pine N17°E 3.05'

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

K-3 Corner common to Sections 1,2,11&12, T31N, R01W

Found ½" bar fitting both of G.F. DeLaMater's and  
Danny M. Bongiovanni witnesses.  
N38°E 2.95' to set N&T on E side 12" W. Pine  
S19°E 46.8' 24" W. Pine stump scribed NBT  
S31°W 72.35' to set N&T at old nail on E side 29" W. Pine

Drove a standard DNR monument over ½" bar.  
Accepted found ½" bar as a careful and faithful  
perpetuation of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-3 Corner common to Sections 1,2,11&12, T31N, R01W

Stamped 4" diameter DNR aluminum cap on 1" x 36"  
galvanized pipe.

Wit N38°E 2.95' to set N&T on E side 12" W. Pine  
S74°E 23.41' to set N&T on S side 5" W. Pine  
S22°W 25.32' to set N&T on E side 11" W. Pine  
N70°W 14.23' to set N&T on N side 6" W. Pine  
S19°E 46.8' 24" W. Pine stump scribed NBT  
S31°W 72.35' to set N&T at old nail on E side 29" W. Pine

Set blue post 1' North

Signed by:

Carl T Kiiskila

Date:

10-14-13

Surveyor's Michigan License No.: 33981

