

OTSEGO COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970
ALSO Act 345, PA 1990

LIBER 0004 PAGE 98

For corners in

OTSEGO
(County)

Located In:

Corner Code ~~77~~

OTSEGO COUNTY
MICHIGAN
RECEIVED FOR RECORD

95 NOV -3 PM 1:39

EVELYN M. PRATT
CLERK / REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T 31 N R 3 W E-11
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____
4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Carl I. Robinson, in a field survey on October 13, 1995
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:


GLO 2/283: Austin Burt, 1850: Set Post-Beech 12" S 22°W 16 lks (10.6'), Sugar 20" N 26°E 33 lks (21.8').
CSR 1/15: J.M. Sanborn, 1882: Sugar 20" N 26°E 33 lks (21.8'), Sugar 8" S 22½°E 42 lks (27.7').
CSR 2/284: G.F. DeLaMater, 1937: Found R.R. Iron- Poplar 24" S 44°E 39.0', Concrete Monument S 45°W 48.0'.
CSR 3/438: S.O. Thorsen (MSHD?), 1958: Found R.R. Rail-Poplar 33" S 44°E 39.2', T.P. S 56°W 52.93', Elm 9" N 13°W 66.3'.
LCRC 2/167: C.I. Robinson, 1980: Fd ½" iron rod, Poplar & T.Pole references, Set Otsego County Monument-
spk 6" R.Pine N 45°E 74.27', spk 48" Poplar S 45°E 39.59', PK T.Pole S 45°W 52.73', tag P.Pole N 45°W 48.77'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Otsego County Monument on approximate extended centerlines on bituminous pavement to south and west,
DeLaMater's Poplar (Cottonwood) & base of Concrete Monument; Thorsen's T.Pole and Robinson's R.Pine & T.Pole.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Otsego County Monument on approximate extended centerlines on bituminous pavement to south & west, accepted as a
careful and faithful perpetuation of the position of the original corner-spk 10" R. Pine N 54°E 74.27', spk & tag
40" Cottonwood S 45°E 39.42', Concrete Monument base S 43°W 48.13', PK T.Pole S 56°W 52.73', spk P.Pole N 49°W 48.91'.



OTSEGO COUNTY REMONUMENTATION

Approved by the County Survey Peer
Group, pursuant to Act 345, PA 1990.

11/2/95 David E. Sawyer
Date V. Chairman

Signed by Carl I. Robinson
Carl I. Robinson, PE & PS, Otsego County Surveyor
Surveyor's Michigan License No. 16390

October 19, 1995