

OTSEGO COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE

LIBER 0004 PAGE 138

For corners in

Filing Requirement of Act 74, Mich. P.A. 1970  
ALSO Act 345, PA 1990

OTSEGO COUNTY,  
MICHIGAN  
RECEIVED FOR RECORD

95 DEC -6 PM 1:31

EVAN M. PRATT  
CLERK / REGISTER OF DEEDS

OTSEGO  
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 31 N R 3 W I-9

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Carl I. Robinson, in a field survey on November 20, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO 2/280: Austin Burt, 1850: Set Post-Sugar 12" S 57°W 9 lks (5.9'), Sugar 7" N 49°E 44 lks (29.0').

CSR 2/210: G.F. DeLaMater, 1920: Found both B's & P, Sugar Post in fill-Sugar 5" N 55 3/4° E 77 lks (50.8'), Sugar 6" N 60°W 73 lks (48.2').


LCRC 1/433: G.R. McKelvey, 1974: Found 1/2" iron and DeLaMater's blazed Maple N 56°E 50.88' & N 60°W 48.96', set Concrete Monument-tag 6" Maple N 19°E 10.85', tag 8" Maple S 75°W 24.73', tag 12" Maple N 27°W 13.78'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Concrete Monument in fill, both of DeLaMater's blazed Sugar's (Maples), and both of McKelvey's references.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Capped Concrete Monument in fill 2'± south of centerline of old trail road-Steel Fence Post S 80°W 0.5'±, spk 11" Maple N 19°E 12.52', spk 16" Maple N 56°E 51.38', nail 10" Maple S 31°E 17.22', spk 17" Maple N 27°W 14.32'. Accepted as a careful and faithful perpetuation of the position of the original corner.



OTSEGO COUNTY REMONUMENTATION

Approved by the County Survey Peer  
Group, pursuant to Act 345, PA 1990.

11/27/95 Date David E. Sargent  
V. Chairman

Signed by

Carl I. Robinson

Date November 22, 1995

Surveyor's Michigan License No. 16390