

SURVEY &
REMONUMENTATION

OCT 07 1996

OTTAWA COUNTY REMONUMENTATION

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in OTTAWA

(County)	Located In:	Corner Code ##
	6N 13W	M-3 (SE 1/4 cor
1. Public Land Survey	T _____ R _____	Section 1)
	T _____ R _____	Georgetown Twp.
	T _____ R _____	
	T _____ R _____	
2. Property Controlling	S _____ T _____ R _____	
in Section	S _____ T _____ R _____	
3. Miscellaneous	S _____ T _____ R _____	
Property in Sec.	S _____ T _____ R _____	

RECORDED

96 AUG 26 PM 2:00

Randy J. Vugteveen
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Randal J. Vugteveen, in a field survey on January 4, 1996,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

M-3 Common corner to Section 12, 6 & 7 of T6N, R12W

1837 - Sibley

Set post

W Oak 22N 4

Liber 3, Page 6

Square spike in SW side of 28" Maple NE 40.80'

Nail in bottle cap in NE side of 42" Catalpa SE 75.92'

PK in NW side of pp SW 43.54'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found KC mon @ centerline "X" Kenowa & Burton, accepted as a careful and faithful perpetuation of the position of the original corner

KCRM nail & tag in NE side of 42" Sycamore SE
75.94'

Held as common corner with A-3, T6N, R12W, Kent
Co, per witnesses on LCRC #202, #1445, #5697,
#7388 and per L. 3, Pg 6 and Gov't Survey Map

PEER APPROVED 5-20-96

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-3 - Kent County Harrison Monument

Set Ottawa County Remon Nail & Tag NW side light pole Az. 51 deg 41.82'

Set Ottawa County Remon Nail & Tag above KCRM nail & tag SW side 40" Sycamore Az. 138 deg 75.94'

Set Ottawa County Remon Nail & Tag above KCRM nail & tag NW side 16" W. Pine Az. 228 deg. 55.36'

Set Ottawa County Remon Nail & Tag NE side 24" Maple Az. 326 deg. 45.81'



Signed by Randal J. Vugteveen

Date MAY 20, 1996

Surveyor's Michigan License No. 28429