

DEC 16 1996

COMMISSION

**OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

<u>Ottawa</u> (County)	Located In: Robinson Twp.	Corner Code #
1. Public Land Survey	T <u>7N</u> R <u>15W</u>	B-13
	T <u> </u> R <u> </u>	S <u>1/4</u> corner
	T <u> </u> R <u> </u>	Section <u>31</u>
	T <u> </u> R <u> </u>	
2. Property Controlling in Section	S <u> </u> T <u> </u> R <u> </u>	
	S <u> </u> T <u> </u> R <u> </u>	
3. Miscellaneous Property in Sec.	S <u> </u> T <u> </u> R <u> </u>	
	S <u> </u> T <u> </u> R <u> </u>	

RECORDED

96 NOV 14 AM 11:21

Phyllis Robinson
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Carl P. Englert, in a field survey on 9/10, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

B-13 South 1/4 corner Section 31
1832 by Sylvester Sibley

Set 1/2 mile Post
Blk Ash 6" N15°W 11 Links
W. Ash 14" N80°W 15 Links
See other side of page

LCRC Liber 4, Page 56
May 15, 1980
Found Cast Iron Monument
1" pipe North 33.0'
12" Ash North 23.8'
28" Oak W.S.W. 58.3'
Olive Cor. West 191.38'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-13 South 1/4 corner Section 31

Found 3" Harrison Cast Iron Monument in Mon. Box
Found P.K. Nail in W. Side 20" Oak North 97.95'
Found 12" Maple SE 42'±
Found 24" Oak SSW 57'±
Found Nail in W. Side P.P. NW 42.96'

P.A. 345 OTTAWA COUNTY

PEER APPROVED 9-16-96
G.D.N.

Accepted as a careful and faithful perpetuation of the original position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-13 S 1/4 corner Section 31


3" Harrison Cast Iron Monument in Mon. Box 6" Deep in Road Centerline	
O.C. Remon. Tag & Nail in W. side P.P.	N14°W 42.97'
O.C. Remon. Tag & Nail in W. side 24" Oak	N01°W 97.95'
O.C. Remon. Tag & Nail in SE. side P.P.	N52°E 72.60'
O.C. Remon. Tag & Nail in SE. side 10" Maple	S61°W 58.00'
O.C. Remon. Tag & Nail in SW. side 12" Maple	S43°E 41.96'

Signed by

Carl P. Englert

Date Sept. 11, 1996

Surveyor's Michigan License No. 18987



SURVEY &
REMONUMENTATION

DEC 18 1996

COMMISSION

B-13 S 1/4 corner Section 31, T7N, R15W
LCRC Liber 6, Page 75 December 21, 1990
Found Cast Mon.

W. 191.38 to Olive Corner

N. 97.95 to P.K. Nail W. Side 20" Oak

NE. 48.23 to Nail W. Side 8" Pine

SE. 42.19 to Nail E. Side 10" Maple

SSW. 56.80 to Nail E. Side 24" Oak

NW. 42.96 to Nail W. Side P. Pole