

SURVEY & REMONUMENTATION

DEC 16 1996

COMMISSION

For corners in

OTTAWA COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Ottawa
(County)

Located In: Robinson Township
Corner Code #

1. Public Land Survey

T 7N R 15W

G-10

T R

E. 1/4 corner

T R

Section 28

T R

2. Property Controlling
in Section

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

RECORDED

95 NOV 14 AM 11:20

Register of Deeds
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Carl P. Englert, in a field survey on 9/12, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

G-10 1/4 corner common to Sections 27 & 28
G.L.O. May 1832 by Calvin Britain
Set 1/2 mile post
Tamarack 6" S70°E 85 links
Pine 10" S62°W 45 links

LCRC Liber 2, Pg. 415, Nov. 1973
Found P.K. Nail Set 5/8" Rod
E.N.E. 32.13 14" Spruce
S.W. 52.00 P.P.
N.W. to N.E. Cor. Endwall 30.10'
LCRC Liber 6, Pg. 58, Oct. 1990
Fd 5/8" Iron Set C.I.M.
Nail in Guy P. S.W. 54.37'
Nail in P.P. N.E. 51.77'
P.K. Nail in F.P. S.E. 46.90'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-10 1/4 corner common to Sections 27 & 28
Found Cast Iron Monument in Mon. Box in pavement Centerline
Found N.E. Cor. Endwall N.W. 30.10'
Found P.K. in fence post S.E. 47'±
On centerline of Gravel road West

P.A. 345 OTTAWA COUNTY
PEER APPROVED 9/16/96
C.P. Englert

Accepted as a careful and faithful perpetuation of the original position of the corner

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10 1/4 corner common to Sections 27 & 28
4" Harrison Cast Iron Monument in Mon. Box 3" deep
O.C. Remon tag & nail in E. side P.P. N18°E 161.25'
O.C. Remon tag & nail in S.W. side 6" Aspen S44°E 61.22'
O.C. Remon tag & nail in S.E. side 16" Pine S67°W 91.39'
O.C. Remon tag & nail in N.E. side 16" Pine N57°W 78.71'



Signed by Carl P. Englert Jr.
Surveyor's Michigan License No. 18987

Date 9/16/1996