## SURVEY & REMONUMENTATION

APR 2 4 1995

4. Lot No. \_\_\_\_\_, Recorded Plat \_

5. Private Claims \_\_\_

OTTAWA COUNTY REMONUMENTATION

## COMMISSION

For corners in

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

94 DEC 15 AM11: 51

RECORDED

Den	yelis	andimon	į
	REGISTE OTTAWA	R OF DEEDS COUNTY, MI	

_0	ttawa (County)	Located In: Robinson Twp.	Corner Code ##
1.	Public Land Survey	T <u>7N</u> R <u>15W</u> T R T R T B	K-7 SW Corner Section 13
2.	Property Controlling in Section	S T R S T R	
3.	Miscellaneous Property in Sec.	S T R S T R	

Register of Deeds Stamp & File Number

i, <u>Carl P. Engler</u> in a field survey on _ do hereby certify that under requirements of P.A. 74, Mic		
in lines 1 and 2 above were in conformance with regu current manual of survey instructions of the United Sta	ulations and rules therefore	as required in the

Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-7 corner common to Sections 13,14,23 & 24 Original Gov't corner set May 1832

by Calvin Britain D.S.

Set corner Hemlock 12" S5620E 5 Links 20" N56 20W 7 Links Liber 5, Page 94

K-8

Set Cast Iron monument

12

Twin 12" Maple E.S.E. 46.18' S.E. 43.331

ΤP

49.15' S.W.

Street Sign P.P.

N.W.

See Back of Page B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-7 corner common to Sections 13, 14, 23 & 24
Found 3" Harrison Cast Iron Mon. in Mon. Box at £ intersection 6" deep.

Found P.P. S.W. 66.03'

Found P.P. N.W. 76.20' (No Nail)

P.A. 345 OTTAWA COUNTY

PEER APPROVED\_\_\_

Accepted as a careful and faithful perpetuation of the original position of the corner.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
  - K-7 corner common to Sections 13,14,23 & 24

    - 3" Harrison Cast Iron Mon. in Mon. Box
      O.C. Remon. Tag & Nail in W. Side 28" Pine S11°E 170.44'
      O.C. Remon. Tag & Nail in N.W. Side 30" Oak N42°E 49.63'
      O.C. Remon. Tag & Nail in S.W. Side P.P. N25°W 76.00'

    - O.C. Remon. Tag & Nail in W. Side 28" Maple N79°W 200.22'

annunnanning and a second ATE CARLE ENGLERT JR. **PROFESSIONAL** SURVEYOR No. 18987 WONAL SU WWW. SO.

BEVISED JAN., 1983

Signed by Carl P. En	gleeth
Surveyor's Michigan License No.	

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975

## Liber 2, Page 169

K-7
Set cast iron monument
P.P. S.W. 66.03'
P.P. N.W. 76.20'
20" Oak N.E. 29.55'
28" Maple S.E. 56.73'