

SURVEY &
REMONUMENTATION

NOV 10 1993

COMMISSION

OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED

1993 SEP 29 PM 3:14

Phyllis L. Lathrop
REGISTER OF DEEDS
OTTAWA COUNTY, MI

For corners in
Ottawa

(County)

Located In:

Corner Code =#

1. Public Land Survey T 8N R 13W I-5 (NE, 15)
T R Wright Twp.
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, Donald W. Schiele, in a field survey on Sept 17, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-5 corner common to Sections 10, 11, 14 and 15 Wright Twp.
L.C.R.C. recorded in Liber 3, Page 62
C.I.M. in Mon. Box
14" Birch SE. 83.00'
P. Pole SW. 57.30'
Tel. Pole NE. 61.90'
CL St. sign N. 27.25'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-5
Found C.I.M. in Monument Box Inscribed "Ottawa County Section Corner" and accepted as a careful and faithful perpetuation of the position of the original corner.
Found PK nail in SE side of Power Pole SW 57.44'
Found PK nail in NW side of Power Pole SW 57.65'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-5
C.I.M. 2" below surface in Monument Box
Set nail and Ottawa Co. re-mon. tag in North side of Power Pole S75°E 174.37'
Set nail and Ottawa Co. re-mon. tag in SW side of 20" Spruce S30°E 82.30'
Set nail and Ottawa Co. re-mon. tag in East side of 12" Maple S17°W 98.05'
Set nail and Ottawa Co. re-mon. tag in SE side of Power Pole S45°W 59.45'
CL gravel road South East 3'
On CL East and West asphalt road

Signed by

Donald W. Schiele

Date

SEPT. 20, 1993

Surveyor's Michigan License No.

23517

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 24, 1975
REVISED MAY 1975
JAN 25 JAN., 1983